



# API USER JOURNEY- CONTENT

**Version 3.1**

## Contents

Page

### Table of Contents

1.	CONTENT API.....	6
1.1.	Attribute Index.....	6
1.2.	Samples for businessHour data.....	10
2.	Content Provider API.....	17
2.1.	Accommodation.....	17
	createAccommodation.....	17
	deleteAccommodation.....	19
	updateAccommodation.....	20
2.2.	Attractions.....	25
	createAttractions.....	25
	deleteAttractions.....	27
	updateAttractions.....	28
2.3.	Bars and Clubs.....	34
	createBarsClubs.....	34
	deleteBarsClubs.....	37
	updateBarsClubs.....	38
2.4.	Cruises.....	43
	createCruises.....	43
	deleteCruises.....	44
	updateCruises.....	45
2.5.	Events.....	47
	createEvent.....	47
	createEventDetails.....	49
	deleteEvent.....	50
	deleteEventDetail.....	50
	updateEvent.....	51
	updateEventDetails.....	53
2.6.	Food and Beverages.....	57
	createFoodBeverages.....	57
	deleteFoodBeverages.....	59

	updateFoodBeverages.....	59
2.7.	Malls and Shops .....	65
	createShops .....	65
	deleteShops .....	67
	updateShops .....	67
2.8.	Precincts .....	73
	createPrecincts .....	73
	deletePrecinct.....	74
	updatePrecincts .....	75
2.9.	Tours.....	80
	createTour .....	80
	deleteTour .....	82
	updateTour .....	82
2.10.	Venues.....	88
	createVenue .....	88
	deleteVenue .....	89
	updateVenue .....	91
2.11.	Walking Trails .....	96
	createWalkingTrail.....	96
	createWalkingTrailDetails.....	98
	deleteWalkingTrail.....	100
	deleteWalkingTrailDetail .....	100
	updateWalkingTrail .....	101
	updateWalkingTrailDetails .....	103
3.	Content User API .....	107
3.1.	General.....	107
	autoCompleteByType .....	107
	getTags.....	107
	listDatasets .....	108
	searchCompanyByKeyword .....	108
	searchKeywordByMultiDataset .....	109
3.2.	Accommodation .....	110
	getAccommodationByUuids .....	110

	listAccommodationTypes .....	111
	searchAccommodationByKeyword.....	111
3.3.	Attractions.....	113
	getAttractionsByUuids.....	113
	listAttractionsTypes .....	113
	searchAttractionsByKeyword .....	114
3.4.	Bars and Clubs.....	115
	getBarsClubsByUuids .....	115
	listBarsClubsTypes .....	115
	searchBarsClubsByKeyword .....	116
3.5.	Cruises .....	117
	getCruisesByUuids .....	117
	searchCruisesByKeyword.....	118
	listCruisesTypes .....	119
3.6.	Events.....	120
	getEventByUuids.....	120
	getEventDetailsByUuid .....	120
	listEventTypes.....	121
	searchEventByKeyword .....	121
3.7.	Food & Beverages .....	122
	getFoodBeveragesByUuids .....	122
	listFoodBeveragesTypes .....	122
	searchFoodBeveragesByKeyword .....	123
3.8.	Malls and Shops .....	124
	getShopsByUuids .....	124
	listShopsTypes .....	124
	searchShopsByKeyword.....	125
3.9.	Precincts.....	126
	getPrecinctsByUuids .....	126
	searchPrecinctsByKeyword.....	127
	searchByPrecinctUuid.....	128
3.10.	Tours.....	130
	getTourByUuids .....	130

---

listTourTypes .....	130
searchTourByKeyword.....	131
3.11. Venues.....	132
getVenueByUuids .....	132
listVenueTypes.....	132
searchVenueByKeyword.....	133
3.12. Walking Trails.....	134
getWalkingTrailByUuids.....	134
getWalkingTrailDetailsByUuid .....	135
listWalkingTrailTypes .....	135
searchWalkingTrailByKeyword .....	136

## REVISION HISTORY

Version	Date	Summary
1.0	11/03/2018	Base Version <ul style="list-style-type: none"> <li>- Content Provider API published as part of Provider API User Journey technical documentation.</li> <li>- Content User API published as part of Consumer API User Journey technical documentation.</li> </ul>
2.0	12/11/2018	Revision – TIH2.0 <ul style="list-style-type: none"> <li>- Added 2 new content categories               <ul style="list-style-type: none"> <li>o Events and Venues</li> </ul> </li> <li>- Support multi-language content               <ul style="list-style-type: none"> <li>o Chinese, Japanese and Korean</li> </ul> </li> <li>- Introduced structured data format               <ul style="list-style-type: none"> <li>o Opening Hours data field</li> </ul> </li> <li>- Search by Multiple Dataset</li> </ul>
3.0	12/04/2019	Revision <ul style="list-style-type: none"> <li>- Technical Documentation created with regrouping of APIs, with this document specifically created for group of APIs under Content, which contains:               <ul style="list-style-type: none"> <li>o Content Provider API</li> <li>o Content User API</li> </ul> </li> <li>- Included new content category:               <ul style="list-style-type: none"> <li>o Precincts</li> </ul> </li> <li>- Removed deprecating APIs (from Content User API):               <ul style="list-style-type: none"> <li>o getCompanyByCode</li> <li>o searchByKeyword</li> <li>o searchByDataset</li> <li>o get(Category)ByName</li> <li>o search(Category)ByTags</li> <li>o search(Category)ByTypeAndKeyword</li> </ul> </li> </ul>
3.1	21/05/2019	Revision – TIH3.2 <ul style="list-style-type: none"> <li>- Added new content category               <ul style="list-style-type: none"> <li>o Cruises</li> </ul> </li> </ul>

## 1. CONTENT API

Content APIs allow applications to contribute and extract data from the Tourism Information and Services Hub (TIH).

### 1.1. Attribute Index

When an API is invoked, a JSON-formatted response is returned to the user. The table below provides a brief overview on all the attributes commonly found in the response.

Main Attribute	Sub-Attribute	Description	Example
address	block	Address where the record is located in Singapore	1
	streetName		Chinese Garden Rd
	floorNumber		
	unitNumber		
	buildingName		
	postalCode		619795
name		Name of the record	Chinese Garden
location	latitude	Latitude and longitude values provided by user, based on this we search on specific place or nearby	1.3130097
	longitude		103.7892928
type		Type in which the record belongs to	RECREATION_LEISURE
tags		Tags pertaining to the record	Jurong
description		Text description of the record	Chinese Garden is a park in Jurong East, Singapore. Built in 1975 by the JTC Corporation and designed by Prof. Yuen-chen Yu, an architect from Taiwan, the Chinese Garden's concept is based on Chinese gardening art.
typeDescription		type description of the record	Leisure & Recreation
source		Name of organization that posted the record	STB

metadata	createdDate	Date in which the record was created in the server	2017-10-30T20:20:00Z
	updatedDate	Date in which the record was last updated in the server	2017-08-11T15:21:00Z
singaporeTourismAwards		Field to indicate the awarded Singapore Tourism Award	2016 - BEST ATTRACTION EXPERIENCE
rating		Google rating of that particular record, out of 5 stars	5

thumbnails	url	When uploading thumbnails to TIH Repository using media image api, it will return image url & unique identifier details in response	<a href="https://tih-api.stb.gov.sg/media/v1/download/uuid/101fd529ef999964f66bf9283a06b266a26/thumbnails.jpg">https://tih-api.stb.gov.sg/media/v1/download/uuid/101fd529ef999964f66bf9283a06b266a26/thumbnails.jpg</a>
	uuid		101b9697999b61344e8833776a98d886761
images	url	When uploading images to TIH Repository using media image api, it will return image url & unique identifier details in response	<a href="https://tih-api.stb.gov.sg/media/v1/download/uuid/101fd529ef999964f66bf9283a06b266a26/thumbnails.jpg">https://tih-api.stb.gov.sg/media/v1/download/uuid/101fd529ef999964f66bf9283a06b266a26/thumbnails.jpg</a>
	uuid		101b9697999b61344e8833776a98d886761
videos	url	When uploading images to TIH Repository using media video api, it will return video url & unique identifier details in response	<a href="https://tih-api.stb.gov.sg/media/v1/download/uuid/101fd529ef999964f66bf9283a06b266a26/thumbnails.jpg">https://tih-api.stb.gov.sg/media/v1/download/uuid/101fd529ef999964f66bf9283a06b266a26/thumbnails.jpg</a>
	uuid		101b9697999b61344e8833776a98d886761



body			Chinese Garden is a park in Jurong East, Singapore. Built in 1975 by the JTC Corporation and designed by Prof. Yuen-chen Yu, an architect from Taiwan, the Chinese Garden's concept is based on Chinese gardening art.
uuid		Unique ID attribute used to uniquely identify a record	00290ed83551389471abe25eecf4ddb9563
contact	primaryContactNo	Contact details pertaining to the record	+65 6466 4911
	secondaryContactNo		+65 6466 4911
	otherContactNo		+65 6466 4911
officialEmail		The official email of the record	stb@gmail.com
ticketed			No
amenities		Available facilities of the record	Swimming Pool
nearestMrtStation		The nearest MRT Station to the record	Chinese Garden MRT Station
officialWebsite		The official website of the record	<a href="http://www.visitsingapore.com/content/traveller/en/browse/seeand-do/nature-andwildlife/parks-andgardens/chinesegarden/">http://www.visitsingapore.com/content/traveller/en/browse/seeand-do/nature-andwildlife/parks-andgardens/chinesegarden/</a>
shortDescription		A short description to provide a summary of the record	Chinese Garden is a park in Jurong East, Singapore.
pricing		Pricing information of the record	child \$12, others \$20, seniorCitizen \$12, adult \$18
admissionInfo		Any information related to the admission to the record	Open on all days

openingHours	<p>Opening and closing hours of the record</p> <p><u>Format:</u>            Opening and Closing hours of the record.            Open 24 Hours            Open DDD-DDD            HH:MMa - HH:MMa            DDD-DDD HH:MMa - HH:MMa            Open Public Holiday            HH:MMa - HH:MMa            Open DDD-DDD            HH:MMa</p>	<p>Mon-Sun:24hours             Mon-Wed 12:00am-4:00pm            Fri-Sun 12:00am-4:00pm             Public Holiday 12:00am-4:00pm             Mon-Sun 12:00am-4:00pm</p>
--------------	---	--

For older APIs, under General and other categories (except Precincts) that accepts “nextToken” input parameter, the API response will return nextToken value that can be used to obtain subsequent records.

nextToken	<p>Next token which can be used to obtain the subsequent set of <b>N</b> records</p>	<p>MNXW2LTTORRC45DJNAX            GG33SMUXG233EMVWC4            QLUORZGCY3UNFXW4UTF            MZJWKYLSMNUFEZLTOVW            HIJJXIMSTOQZRG13SKN2DE            U3UGMRQEU3UGJXIMZD            AJJXIMSTOQ3UPFYGKJTIQ            STOQZFG5BWWZLZO5XXEZ            BFGNCGCJJXIMSTOQ3EMF            2GC43POVZGGZJFGNCKN            2DEU3UG</p>
-----------	--	---

For new APIs under Precincts category that accepts “page” and “pageSize” input parameter, the API response will return total records and total pages to facilitate developer to display pagination information, details as below.

totalRecords	Total number of records.	33
totalPages	Total number of pages.	3

## 1.2. Samples for businessHour data

Additional samples for business hour (**businessHour**), in JSON StructureJSON format:

a. Daily open (24h) including public holiday

```
"businessHour": [  
  {  
    "day": "daily",  
    "openTime": "00:00",  
    "closeTime": "23:59",  
    "description": "",  
    "sequenceNumber": 1,  
    "daily": true  
  }  
],  
"notes": "",
```

b. Daily open (time based) including public holiday

```
"businessHour": [  
  {  
    "day": "daily",  
    "openTime": "08:30",  
    "closeTime": "20:30",  
    "description": "",  
    "sequenceNumber": 1,  
    "daily": true  
  }  
],  
"notes": "",
```

c. Daily (24h) with public holiday open

```
"businessHour": [  
  {  
    "day": "daily",  
    "openTime": "00:00",  
    "closeTime": "23:59",  
    "description": "",  
    "sequenceNumber": 1,  
    "daily": true  
  },  
  {  
    "day": "public_holiday",  
    "openTime": "08:30",  
    "closeTime": "14:30",  
    "description": "",  
    "sequenceNumber": 2,  
    "daily": false  
  }  
],  
"notes": "",
```

d. Daily (time based) with public holiday open

```
"businessHour": [  
  {  
    "day": "daily",  
    "openTime": "08:30",  
    "closeTime": "20:30",  
    "description": "",  
    "sequenceNumber": 1,  
    "daily": true  
  },  
  {  
    "day": "public_holiday",  
    "openTime": "08:30",  
    "closeTime": "15:30",  
    "description": "",  
    "sequenceNumber": 2,  
    "daily": false  
  }  
],  
"notes": "",
```

---

e. Daily open with multiple public holidays

```
"businessHour": [  
  {  
    "day": "daily",  
    "openTime": "00:00",  
    "closeTime": "23:59",  
    "description": "",  
    "sequenceNumber": 1,  
    "daily": true  
  },  
  {  
    "day": "public_holiday",  
    "openTime": "09:30",  
    "closeTime": "15:30",  
    "description": "Chinese New Year",  
    "sequenceNumber": 2,  
    "daily": false  
  },  
  {  
    "day": "public_holiday",  
    "openTime": "10:00",  
    "closeTime": "17:00",  
    "description": "New Year's Day",  
    "sequenceNumber": 3,  
    "daily": false  
  }  
],  
"notes": "closed on 1st Chinese New Year",
```

f. Monday to Friday same

```
"businessHour": [  
  {  
    "day": "monday",  
    "openTime": "08:30",  
    "closeTime": "16:30",  
    "description": "",  
    "sequenceNumber": 1,  
    "daily": false  
  },  
  {  
    "day": "tuesday",  
    "openTime": "08:30",  
    "closeTime": "16:30",  
    "description": "",  
    "sequenceNumber": 2,  
    "daily": false  
  },  
  {  
    "day": "wednesday",  
    "openTime": "08:30",  
    "closeTime": "16:30",  
    "description": "",  
    "sequenceNumber": 3,  
    "daily": false  
  },  
  {  
    "day": "thursday",  
    "openTime": "08:30",  
    "closeTime": "16:30",  
    "description": "",  
    "sequenceNumber": 4,  
    "daily": false  
  },  
  {  
    "day": "friday",  
    "openTime": "08:30",  
    "closeTime": "16:30",  
    "description": "",  
    "sequenceNumber": 5,  
    "daily": false  
  },  
  {  
    "day": "public_holiday ",  
    "openTime": "10:00",
```

```
"closeTime": "14:30",  
"description": "",  
"sequenceNumber": 6,  
"daily": false  
}  
],  
"notes": "closed on 1st Chinese New Year",
```

g. 3 continues days with same time

```

"businessHour": [
  {
    "day": "wednesday",
    "openTime": "11:30",
    "closeTime": "14:30",
    "description": "Lunch",
    "sequenceNumber": 1,
    "daily": false
  },
  {
    "day": "wednesday ",
    "openTime": "17:00",
    "closeTime": "20:30",
    "description": "Dinner",
    "sequenceNumber": 2,
    "daily": false
  },
  {
    "day": "friday",
    "openTime": "11:30",
    "closeTime": "14:30",
    "description": "Lunch",
    "sequenceNumber": 3,
    "daily": false
  },
  {
    "day": "friday",
    "openTime": "17:00",
    "closeTime": "20:30",
    "description": "Dinner",
    "sequenceNumber": 4,
    "daily": false
  },
  {
    "day": "saturday",
    "openTime": "11:30",
    "closeTime": "14:30",
    "description": "Launch",
    "sequenceNumber": 5,
    "daily": false
  },
  {
    "day": "saturday ",
    "openTime": "17:00",
    "closeTime": "20:30",
    "description": "Dinner",
    "sequenceNumber": 6,
    "daily": false
  },
  {
    "day": "sunday",
    "openTime": "11:30",
    "closeTime": "14:30",
    "description": "Launch",
    "sequenceNumber": 7,
    "daily": false
  },
  {
    "day": "sunday ",
    "openTime": "17:00",
    "closeTime": "20:30",
    "description": "Dinner",
    "sequenceNumber": 8,
    "daily": false
  },
  {
    "day": "public_holiday ",
    "openTime": "10:00",
    "closeTime": "14:30",
    "description": "Lunch",
    "sequenceNumber": 9,
    "daily": false
  }
],
"notes": "Buffet dinner menu only available on
Friday, Saturday, Sunday",

```



#### h. Monday to Sunday same time

```

"businessHour": [
  {
    "day": "monday",
    "openTime": "09:00",
    "closeTime": "17:30",
    "description": "",
    "sequenceNumber": 1,
    "daily": false
  },
  {
    "day": "tuesday",
    "openTime": "09:00",
    "closeTime": "17:30",
    "description": "",
    "sequenceNumber": 2,
    "daily": false
  },
  {
    "day": "wednesday",
    "openTime": "09:00",
    "closeTime": "17:30",
    "description": "",
    "sequenceNumber": 3,
    "daily": false
  },
  {
    "day": "thrusday",
    "openTime": "09:00",
    "closeTime": "17:30",
    "description": "",
    "sequenceNumber": 4,
    "daily": false
  },
  {
    "day": "friday",
    "openTime": "09:00",
    "closeTime": "17:30",
    "description": "",
    "sequenceNumber": 5,
    "daily": false
  },
  {
    "day": "saturday ",
    "openTime": "09:00",
    "closeTime": "17:30",
    "description": "",
    "sequenceNumber": 6,
    "daily": false
  },
  {
    "day": "sunday",
    "openTime": "09:00",
    "closeTime": "17:30",
    "description": "",
    "sequenceNumber": 7,
    "daily": false
  },
  {
    "day": "public_holiday ",
    "openTime": "10:00",
    "closeTime": "14:30",
    "description": "",
    "sequenceNumber": 8,
    "daily": false
  }
],
"notes": "closed on 1st Chinese New Year",

```

## 2. Content Provider API

### 2.1. Accommodation

The APIs listed below allow contribution of Accommodation Points of Interest (POIs) and its details (e.g. type, amenities, room rates) Accommodation POIs can be retrieved by uuid or keyword search thereafter.

<div> <div>POST</div> <div> <b>createAccommodation</b>  <a href="https://tih-api.stb.gov.sg/content/v1/admin/accommodation">https://tih-api.stb.gov.sg/content/v1/admin/accommodation</a> </div> </div>		
Allows the creation of an Accommodation POI. To create successfully, the following input parameters are mandatory: name, type, tags, description and body.		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Accommodation to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "uuid": "",   "name": "Aqueen Heritage Hotel Joo Chiat",   "type": "Hotels",   "tags": ["Central"],   "description": "Field to describe the record, Example: The hotel, a   refurbished 1920s colonial building with a wedge-shaped structure akin to New   York's Flatiron Building, is located near many shophouse eateries.",   "location": {     "latitude": "1.287",     "longitude": "103.805"   },   "address": {     "block": "323",     "streetName": "Alexandra Road",     "floorNumber": "1",     "unitNumber": "323",     "buildingName": "Alexandra Point",     "postalCode": "159972"   },   "thumbnails": [ {     "uuid": "",     "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c 52"</pre>		

```

    }
  ],
  "images": [ {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
  "documents": [ {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
  "contact": {
    "primaryContactNo": "+65 6828 8888",
    "secondaryContactNo": "",
    "otherContactNo": ""
  },
  "nearestMrtStation": "Paya Lebar MRT Station",
  "officialWebsite": "http://www.aqueenhotels.com/",
  "officialEmail": "info@aqueenhotels.sg",
  "body": "Aqueen Heritage Hotel Joo Chiat is housed in a 1920s colonial building with a unique wedge shaped structure said to be similar to New York's famous Flatiron Building. The hotel is located in the historic district of Katong and Joo Chiat and its interiors reflect the area's heritage, with dark wood furnishings, the use of Peranakan motifs and displays of old photographs. In the vicinity are well preserved pre-war shophouses, many of which have been converted into traditional eateries, modern cafés and bars. About five minutes' walk away is Geylang Serai Market and Food Centre, which has reasonably priced Indian and Malay food. Supermarkets and shopping malls such as OneKM Mall are also within walking distance. Guests staying for two nights or more will receive a prepaid mobile card with credit, local data and free calls to 19 destinations worldwide.",
  "videos": [ {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
  "leadInRoomRates": "$150",
  "noOfRooms": 70,
  "leadInRoomSize": "14sqm",
  "amenities": "Wheelchair Accessible",
  "supportedLanguage": "en"
}

```

# DELETE

## deleteAccommodation

<https://tih-api.stb.gov.sg/content/v1/admin/accommodation/{uuid}>

Allows the deletion of an existing Accommodation POI through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchAccommodationByKeyword API.

### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify an accommodation	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

### Example

```
{
  "uuid": "00173690421773247079f4441487b811fd6",
  "language": "EN",
}
```

PUT

updateAccommodation  
https://tih-api.stb.gov.sg/content/v1/admin/accommodation/{uuid}

Allows an existing Accommodation POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchAccommodationByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify an accommodation. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Accommodation to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

```
{  "uuid": "00173690421773247079f4441487b811fd6",  "name": "Aqueen Heritage Hotel Joo Chiat",  "type": "Hotels",  "tags": ["Central"],  "description": "Field to describe the record, Example: The hotel, a refurbished 1920s colonial building with a wedge-shaped structure akin to New York's Flatiron Building, is located near many shophouse eateries.",  "location": {    "latitude": "1.287",    "longitude": "103.805"  },  "address": {    "block": "323",    "streetName": "Alexandra Road",    "floorNumber": "1",    "unitNumber": "323",    "buildingName": "Alexandra Point",    "postalCode": "159972"  },  "thumbnails": [ {    "uuid": "",    "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"  } ],  "images": [ {    "uuid": "",
```

```

    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
  "documents": [ {
    "uuid": "",
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
  "contact": {
    "primaryContactNo": "+65 6828 8888",
    "secondaryContactNo": "",
    "otherContactNo": ""
  },
  "nearestMrtStation": "Paya Lebar MRT Station",
  "officialWebsite": "http://www.aqueenhotels.com/",
  "officialEmail": "info@aqueenhotels.sg",
  "body": "Aqueen Heritage Hotel Joo Chiat is housed in a 1920s colonial building with a unique wedge shaped structure said to be similar to New York's famous Flatiron Building. The hotel is located in the historic district of Katong and Joo Chiat and its interiors reflect the area's heritage, with dark wood furnishings, the use of Peranakan motifs and displays of old photographs. In the vicinity are well preserved pre-war shophouses, many of which have been converted into traditional eateries, modern cafés and bars. About five minutes' walk away is Geylang Serai Market and Food Centre, which has reasonably priced Indian and Malay food. Supermarkets and shopping malls such as OneKM Mall are also within walking distance. Guests staying for two nights or more will receive a prepaid mobile card with credit, local data and free calls to 19 destinations worldwide.",
  "videos": [ {
    "uuid": "",
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
  "leadInRoomRates": "$150",
  "noOfRooms": 70,
  "leadInRoomSize": "14sqm",
  "amenities": "Wheelchair Accessible",
  "supportedLanguage": "en"
}

```

## Accommodation Data Schema:

Parameter Name	Parameter Type	Parameter Description																		
uuid	string	Attribute used to uniquely identify an record. Example: 00290ed83551389471abe25eecf4ddb9563																		
name	string	Name of the record. Example: Aqueen Heritage Hotel Joo Chiat																		
type	string	Type in which the record belongs to. Example: Backpacker Hostels   Hotels   Resorts   Serviced Apartments   Others																		
tags	array	Tags pertaining to the record, each item is a string. Example: [Central]																		
description	string	Field to describe the record Example: The hotel, a refurbished 1920s colonial building with a wedge-shaped structure akin to New York's Flatiron Building, is located near many shophouse eateries.																		
body	string	Content body of the record Example: Aqueen Heritage Hotel Joo Chiat is housed in a 1920s colonial building with a unique wedge shaped structure said to be similar to New York's famous Flatiron Building. The hotel is ...																		
location	object	Location of the record, containing the following properties: <table border="1"> <tr> <td>latitude</td><td>string</td><td>Example: 1.287</td></tr> <tr> <td>longitude</td><td>String</td><td>Example: 103.805</td></tr> </table>	latitude	string	Example: 1.287	longitude	String	Example: 103.805												
latitude	string	Example: 1.287																		
longitude	String	Example: 103.805																		
address	object	Structured address of the record, containing the following properties: <table border="1"> <tr> <td>block</td><td>string</td><td>Example: 323</td></tr> <tr> <td>streetName</td><td>string</td><td>Example: Alexandra Road</td></tr> <tr> <td>floorNumber</td><td>string</td><td>Example: 1</td></tr> <tr> <td>unitNumber</td><td>string</td><td>Example: 1232</td></tr> <tr> <td>buildingName</td><td>string</td><td>Example: Alexandra Point</td></tr> <tr> <td>postalCode</td><td>string</td><td>Example: 159972</td></tr> </table>	block	string	Example: 323	streetName	string	Example: Alexandra Road	floorNumber	string	Example: 1	unitNumber	string	Example: 1232	buildingName	string	Example: Alexandra Point	postalCode	string	Example: 159972
block	string	Example: 323																		
streetName	string	Example: Alexandra Road																		
floorNumber	string	Example: 1																		
unitNumber	string	Example: 1232																		
buildingName	string	Example: Alexandra Point																		
postalCode	string	Example: 159972																		
contact	object	Contact numbers of the record, containing the following properties: <table border="1"> <tr> <td>primaryContactNo</td><td>string</td><td>Example: +65 6828 8888</td></tr> <tr> <td>secondaryContactNo</td><td>string</td><td>Example: +65 6828 8878</td></tr> <tr> <td>otherContactNo</td><td>string</td><td>Example: +65 6828 8868</td></tr> </table>	primaryContactNo	string	Example: +65 6828 8888	secondaryContactNo	string	Example: +65 6828 8878	otherContactNo	string	Example: +65 6828 8868									
primaryContactNo	string	Example: +65 6828 8888																		
secondaryContactNo	string	Example: +65 6828 8878																		
otherContactNo	string	Example: +65 6828 8868																		

thumbnails	array	<p>Image thumbnails to represent the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>						
images	array	<p>Images related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>						
documents	array	<p>Documents related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>						
videos	array	<p>Videos related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>						
officialWebsite	string	The official website of the record. Example: <a href="http://www.aqueenhotels.com/">http://www.aqueenhotels.com/</a>						
officialEmail	String	The official email of the record. Example: <a href="mailto:info@aqueenhotels.sg">info@aqueenhotels.sg</a>						



businessHour	array	<p>Each item is an object describing the opening hour of the record, containing the following properties:</p> <table border="1"> <tr> <td>sequenceNumber</td><td>integer</td><td>Example: 1</td></tr> <tr> <td>day</td><td>string</td><td>Example: MON</td></tr> <tr> <td>daily</td><td>boolean</td><td>Example: false</td></tr> <tr> <td>openTime</td><td>string</td><td>Example: 10:30</td></tr> <tr> <td>closeTime</td><td>string</td><td>Example: 20:00</td></tr> <tr> <td>description</td><td>string</td><td>Example: close on public holidays</td></tr> </table> <p>Please refer to the examples in section <a href="#">1.2</a>.</p>	sequenceNumber	integer	Example: 1	day	string	Example: MON	daily	boolean	Example: false	openTime	string	Example: 10:30	closeTime	string	Example: 20:00	description	string	Example: close on public holidays
sequenceNumber	integer	Example: 1																		
day	string	Example: MON																		
daily	boolean	Example: false																		
openTime	string	Example: 10:30																		
closeTime	string	Example: 20:00																		
description	string	Example: close on public holidays																		
nearestMrtStation	string	The nearest MRT Station to the record. Example: Paya Lebar MRT Station																		
leadInRoomRates	string	Room rates. Example: \$150																		
noOfRooms	integer	Number of rooms. Example: 70																		
leadInRoomSize	string	Room size. Example: 14sqm																		
singaporeTourismAwards	string	Field to declare if the record has been given an award. Example: Y N																		
amenities	string	Useful facilities found in the record. Example: Wheelchair Accessible																		
supportedLanguage	string	Supported language for this POI Example: en   zh-cn   zh-tw   ja   ko																		

## 2.2. Attractions

The APIs listed below allow contribution of Attractions POIs and its details (e.g. type, amenities, business hours). Attraction POIs can be retrieved by uuid or keyword search thereafter.

<div> <div>POST</div> <div> <b>createAttractions</b>  <a href="https://tih-api.stb.gov.sg/content/v1/admin/attractions">https://tih-api.stb.gov.sg/content/v1/admin/attractions</a> </div> </div>		
Allows the creation of an Attractions POI. To create successfully, the following input parameters are mandatory: name, type, tags, description and body.		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Attraction to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "uuid": "",   "name": "Changi Museum",   "type": "History &amp; Culture",   "tags": ["Museums"],   "description": "This museum commemorates the prisoners-of-war and civilian",   "location": {     "latitude": "1.287",     "longitude": "103.805"   },   "address": {     "block": "323",     "streetName": "Alexandra Road",     "floorNumber": "1",     "unitNumber": "323",     "buildingName": "Alexandra Point",     "postalCode": "159972"   },   "thumbnails": [ {     "uuid": "",     "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"   } ],   "images": [ {     "uuid": "",</pre>		

```

    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
  "documents": [ {
    "uuid": "",
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
  "contact": {
    "primaryContactNo": "+65 6828 8888",
    "secondaryContactNo": "",
    "otherContactNo": ""
  },
  "admissionInfo": "Admisssion Info",
  "businessHour": [
    {
      "day": "daily",
      "openTime": "00:00",
      "closeTime": "23:59",
      "description": "",
      "sequenceNumber": 1,
      "daily": true
    }
  ],
  "notes": "",
  "nearestMrtStation": "Changi Airport MRT Station",
  "officialWebsite": "https://www.changimuseum.sg/",
  "officialEmail": "changi_museum@nhb.gov.sg",
  "body": "The Changi Museum documents significant events that occurred during
World War II and the Japanese Occupation of Singapore. Often included in tours
about the city-state's wartime past, the museum also commemorates the
prisoners-of-war (POWs) and civilians who were detained in Changi Prison
during the war. Among the wartime artefacts on display are photographs,
personal letters, replica patchwork quilts with secret codes, artwork by
several detainees and a duplicate of the famous Changi Murals that Stanley
Warren, one of the POWs, painted during his internment. Located in the centre
of the museum is the Changi Chapel, a replica of the one built by the POWs.
Visitors can view an original cross made from a used ammunition casing, as
well as heartfelt notes and mementos left by previous visitors.",
  "videos": [ {
    "uuid": "",
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],

```

```

"pricing": {
  "child": "$15",
  "others": "$15",
  "seniorCitizen": "$15",
  "adult": "$15"
},
"ticketed": "Y",
"amenities": "Wheelchair Accessible",
"supportedLanguage": "en"
}

```

**DELETE**

## deleteAttractions

<https://tih-api.stb.gov.sg/content/v1/admin/attractions/{uuid}>

Allows the deletion of an existing Attraction POI through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchAttractionsByKeyword API.

### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify an attraction	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

### Example

```

{
  "uuid": "002991c0ccc80c04560ba19cc41593a54de",
  "language": "EN",
}

```

PUT

updateAttractions  
https://tih-api.stb.gov.sg/content/v1/admin/attractions/{uuid}

Allows an existing Attraction POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchAttractionsByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify an attraction. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Attraction to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

```
{  "uuid": "002991c0ccc80c04560ba19cc41593a54de",  "name": "Changi Museum",  "type": "History & Culture",  "tags": ["Museums"],  "description": "This museum commemorates the prisoners-of-war and civilian",  "location": {    "latitude": "1.287",    "longitude": "103.805"  },  "address": {    "block": "323",    "streetName": "Alexandra Road",    "floorNumber": "1",    "unitNumber": "323",    "buildingName": "Alexandra Point",    "postalCode": "159972"  },  "thumbnails": [ {    "uuid": "",    "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"  } ],  "images": [ {    "uuid": "",    "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"  } ]}
```

```

    }
  ],
  "documents": [ {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
  "contact": {
    "primaryContactNo": "+65 6828 8888",
    "secondaryContactNo": "",
    "otherContactNo": ""
  },
  "admissionInfo": "Admisssion Info",
  "businessHour": [
    {
      "day": "daily",
      "openTime": "00:00",
      "closeTime": "23:59",
      "description": "",
      "sequenceNumber": 1,
      "daily": true
    }
  ],
  "notes": "",
  "nearestMrtStation": "Changi Airport MRT Station",
  "officialWebsite": "https://www.changimuseum.sg/",
  "officialEmail": "changi_museum@nhb.gov.sg",
  "body": "The Changi Museum documents significant events that occurred during
World War II and the Japanese Occupation of Singapore. Often included in tours
about the city-state's wartime past, the museum also commemorates the
prisoners-of-war (POWs) and civilians who were detained in Changi Prison
during the war. Among the wartime artefacts on display are photographs,
personal letters, replica patchwork quilts with secret codes, artwork by
several detainees and a duplicate of the famous Changi Murals that Stanley
Warren, one of the POWs, painted during his internment. Located in the centre
of the museum is the Changi Chapel, a replica of the one built by the POWs.
Visitors can view an original cross made from a used ammunition casing, as
well as heartfelt notes and mementos left by previous visitors.",
  "videos": [ {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
  "pricing": {
    "child": "$15",
    "others": "$15",

```

```
"seniorCitizen": "$15",  
  "adult": "$15"  
},  
"ticketed": "Y",  
"amenities": "Wheelchair Accessible",  
"supportedLanguage": "en"  
}
```

## Attraction Data Schema:

Parameter Name	Parameter Type	Parameter Description																		
uuid	string	Attribute used to uniquely identify an record. Example: 00290ed83551389471abe25eecf4ddb9563																		
name	string	Name of the record. Example: Changi Museum																		
type	string	Type in which the record belongs to. Example: Adventure Arts History & Culture Leisure & Recreation Nature & Wildlife Others																		
tags	array	Tags pertaining to the record, each item is a string. Example: [Museums]																		
description	string	Field to describe the record Example: This museum commemorates the prisoners-of-war and civilian																		
body	string	Content body of the record Example: The Changi Museum documents significant events that occurred during World War II and the Japanese Occupation of Singapore. Often ...																		
location	object	Location of the record, containing the following properties: <table border="1"> <tr> <td>latitude</td><td>string</td><td>Example: 1.287</td></tr> <tr> <td>longitude</td><td>String</td><td>Example: 103.805</td></tr> </table>	latitude	string	Example: 1.287	longitude	String	Example: 103.805												
latitude	string	Example: 1.287																		
longitude	String	Example: 103.805																		
address	object	Structured address of the record, containing the following properties: <table border="1"> <tr> <td>block</td><td>string</td><td>Example: 323</td></tr> <tr> <td>streetName</td><td>string</td><td>Example: Alexandra Road</td></tr> <tr> <td>floorNumber</td><td>string</td><td>Example: 1</td></tr> <tr> <td>unitNumber</td><td>string</td><td>Example: 1232</td></tr> <tr> <td>buildingName</td><td>string</td><td>Example: Alexandra Point</td></tr> <tr> <td>postalCode</td><td>string</td><td>Example: 159972</td></tr> </table>	block	string	Example: 323	streetName	string	Example: Alexandra Road	floorNumber	string	Example: 1	unitNumber	string	Example: 1232	buildingName	string	Example: Alexandra Point	postalCode	string	Example: 159972
block	string	Example: 323																		
streetName	string	Example: Alexandra Road																		
floorNumber	string	Example: 1																		
unitNumber	string	Example: 1232																		
buildingName	string	Example: Alexandra Point																		
postalCode	string	Example: 159972																		
contact	object	Contact numbers of the record, containing the following properties: <table border="1"> <tr> <td>primaryContactNo</td><td>string</td><td>Example: +65 6828 8888</td></tr> <tr> <td>secondaryContactNo</td><td>string</td><td>Example: +65 6828 8878</td></tr> <tr> <td>otherContactNo</td><td>string</td><td>Example: +65 6828 8868</td></tr> </table>	primaryContactNo	string	Example: +65 6828 8888	secondaryContactNo	string	Example: +65 6828 8878	otherContactNo	string	Example: +65 6828 8868									
primaryContactNo	string	Example: +65 6828 8888																		
secondaryContactNo	string	Example: +65 6828 8878																		
otherContactNo	string	Example: +65 6828 8868																		



thumbnails	array	<p>Image thumbnails to represent the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
images	array	<p>Images related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
documents	array	<p>Documents related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
videos	array	<p>Videos related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
officialWebsite	string	<p>The official website of the record. Example: <a href="https://www.changimuseum.sg/">https://www.changimuseum.sg/</a></p>						
officialEmail	String	<p>The official email of the record. Example: changi_museum@nhb.gov.sg</p>						

businessHour	array	<p>Each item is an object describing the opening hour of the record, containing the following properties:</p> <table border="1"> <tr> <td>sequenceNumber</td><td>integer</td><td>Example: 1</td></tr> <tr> <td>day</td><td>string</td><td>Example: MON</td></tr> <tr> <td>daily</td><td>boolean</td><td>Example: false</td></tr> <tr> <td>openTime</td><td>string</td><td>Example: 10:30</td></tr> <tr> <td>closeTime</td><td>string</td><td>Example: 20:00</td></tr> <tr> <td>description</td><td>string</td><td>Example: close on public holidays</td></tr> </table> <p>Please refer to the examples in section <a href="#">1.2</a>.</p>	sequenceNumber	integer	Example: 1	day	string	Example: MON	daily	boolean	Example: false	openTime	string	Example: 10:30	closeTime	string	Example: 20:00	description	string	Example: close on public holidays
sequenceNumber	integer	Example: 1																		
day	string	Example: MON																		
daily	boolean	Example: false																		
openTime	string	Example: 10:30																		
closeTime	string	Example: 20:00																		
description	string	Example: close on public holidays																		
nearestMrtStation	string	<p>The nearest MRT Station to the record. Example: Changi Airport MRT Station</p>																		
admissionInfo	string	<p>Any information related to the admission to the record. Example: Open on all days</p>																		
pricing	object	<p>Price details for the admission of the different group of people, containing the following properties:</p> <table border="1"> <tr> <td>adult</td><td>string</td><td>Example: 25\$</td></tr> <tr> <td>child</td><td>string</td><td>Example: 15\$</td></tr> <tr> <td>seniorCitizen</td><td>string</td><td>Example: 15\$</td></tr> <tr> <td>others</td><td>string</td><td>Example: 25\$</td></tr> </table>	adult	string	Example: 25\$	child	string	Example: 15\$	seniorCitizen	string	Example: 15\$	others	string	Example: 25\$						
adult	string	Example: 25\$																		
child	string	Example: 15\$																		
seniorCitizen	string	Example: 15\$																		
others	string	Example: 25\$																		
ticketed	string	<p>Field to declare if the admission is ticketed. Example: Y N</p>																		
singaporeTourismAwards	string	<p>Field to declare if the record has been given an award. Example: Y N</p>																		
amenities	string	<p>Useful facilities found in the record. Example: Wheelchair Accessible</p>																		
supportedLanguage	string	<p>Supported language for this POI Example: en   zh-cn   zh-tw   ja   ko</p>																		

## 2.3. Bars and Clubs

The APIs listed below allow contribution of Bars and Clubs POIs and its details (e.g. type, amenities, business hours) found in Singapore. Bars and Clubs POIs can be retrieved by uuid or keyword search thereafter.

POST <b>createBarsClubs</b> <a href="https://tih-api.stb.gov.sg/content/v1/admin/bars-clubs">https://tih-api.stb.gov.sg/content/v1/admin/bars-clubs</a>		
Allows the creation of a Bar or Club POI. To create successfully, the following input parameters are mandatory: name, type, tags, description and body.		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Bars and Clubs to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "uuid": "",   "name": "Crazy Elephant",   "type": "Clubs",   "tags": ["Entertainment"],   "description": "This Clarke Quay stalwart is highly regarded for its penchant for live rock 'n' roll and blues music. Its wooden décor and graffiti give it a rock authenticity that's unique in Singapore, particularly in an area filled with many shiny new establishments.",   "location": {     "latitude": "1.287",     "longitude": "103.805"   },   "address": {     "block": "323",     "streetName": "Alexandra Road",     "floorNumber": "1",     "unitNumber": "323",     "buildingName": "Alexandra Point",     "postalCode": "159972"   },   "thumbnails": [     {       "uuid": "",</pre>		

```

    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
  "images": [
    {
      "uuid": "",
      "url":
      "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
    }
  ],
  "documents": [
    {
      "uuid": "",
      "url":
      "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
    }
  ],
  "contact": {
    "primaryContactNo": "+65 6828 8888",
    "secondaryContactNo": "",
    "otherContactNo": ""
  },
  "businessHour": [
    {
      "day": "daily",
      "openTime": "00:00",
      "closeTime": "23:59",
      "description": "",
      "sequenceNumber": 1,
      "daily": true
    }
  ],
  "notes": "",
  "nearestMrtStation": "Clarke Quay MRT Station",
  "officialWebsite": "http://crazyelephant.sg/",
  "officialEmail": "info@crazyelephant.sg",
  "body": "This Clarke Quay stalwart is highly regarded for its penchant for
live rock 'n' roll and blues music. Its wooden décor and graffiti give it a
rock authenticity that's unique in Singapore, particularly in an area filled
with many shiny new establishments.",
  "videos": [
    {
      "uuid": "",
      "url":
      "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
    }
  ]

```

```
}  
],  
"amenities": "Club Lounge",  
"supportedLanguage": "en"  
}
```

DELETE

deleteBarsClubs

https://tih-api.stb.gov.sg/content/v1/admin/bars-clubs/{uuid}

Allows the deletion of an existing Bars & Clubs POI through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchBarsClubsByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify Bars and Clubs	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

```
{  
  "uuid": "003cfa2bbab86704fe8838779a240665c64",  
  "language": "EN",  
}
```

PUT

updateBarsClubs  
https://tih-api.stb.gov.sg/content/v1/admin/bars-clubs/{uuid}

Allows an existing Bars & Clubs POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchBarsClubsByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify Bars and Clubs. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Bars and Clubs to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

```
{  "uuid": "003cfa2bbab86704fe8838779a240665c64",  "name": "Crazy Elephant",  "type": "Clubs",  "tags": ["Entertainment"],  "description": "This Clarke Quay stalwart is highly regarded for its penchant for live rock 'n' roll and blues music. Its wooden décor and graffiti give it a rock authenticity that's unique in Singapore, particularly in an area filled with many shiny new establishments.",  "location": {    "latitude": "1.287",    "longitude": "103.805"  },  "address": {    "block": "323",    "streetName": "Alexandra Road",    "floorNumber": "1",    "unitNumber": "323",    "buildingName": "Alexandra Point",    "postalCode": "159972"  },  "thumbnails": [    {      "uuid": "",      "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"    }  ],  "images": [
```

```
{
  "uuid": "",
  "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
}
],
"documents": [
{
  "uuid": "",
  "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
}
],
"contact": {
  "primaryContactNo": "+65 6828 8888",
  "secondaryContactNo": "",
  "otherContactNo": ""
},
"businessHour": [
{
  "day": "daily",
  "openTime": "00:00",
  "closeTime": "23:59",
  "description": "",
  "sequenceNumber": 1,
  "daily": true
}
],
"nearestMrtStation": "Clarke Quay MRT Station",
"officialWebsite": "http://crazyelephant.sg/",
"officialEmail": "info@crazyelephant.sg",
"body": "This Clarke Quay stalwart is highly regarded for its penchant for live rock 'n' roll and blues music. Its wooden décor and graffiti give it a rock authenticity that's unique in Singapore, particularly in an area filled with many shiny new establishments.",
"videos": [
{
  "uuid": "",
  "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
}
],
"amenities": "Club Lounge",
"supportedLanguage": "en"
}
```



## Bar & Club Data Schema:

Parameter Name	Parameter Type	Parameter Description																		
uuid	string	Attribute used to uniquely identify an record. Example: 00290ed83551389471abe25eecf4ddb9563																		
name	string	Name of the record. Example: Crazy Elephant																		
type	string	Type in which the record belongs to. Example: Bars Clubs Other																		
tags	array	Tags pertaining to the record, each item is a string. Example: [Entertainment]																		
description	string	Field to describe the record Example: This Clarke Quay stalwart is highly regarded for its penchant for live rock 'n' roll and blues music. Its wooden décor and graffiti give it a rock authenticity that's unique in Singapore, particularly in an area filled with many shiny new establishments.																		
body	string	Content body of the record Example: This Clarke Quay stalwart is highly regarded for its penchant for live rock 'n' roll and blues music. Its wooden décor ...																		
location	object	Location of the record, containing the following properties: <table border="1"> <tr> <td>latitude</td><td>string</td><td>Example: 1.287</td></tr> <tr> <td>longitude</td><td>String</td><td>Example: 103.805</td></tr> </table>	latitude	string	Example: 1.287	longitude	String	Example: 103.805												
latitude	string	Example: 1.287																		
longitude	String	Example: 103.805																		
address	object	Structured address of the record, containing the following properties: <table border="1"> <tr> <td>block</td><td>string</td><td>Example: 323</td></tr> <tr> <td>streetName</td><td>string</td><td>Example: Alexandra Road</td></tr> <tr> <td>floorNumber</td><td>string</td><td>Example: 1</td></tr> <tr> <td>unitNumber</td><td>string</td><td>Example: 1232</td></tr> <tr> <td>buildingName</td><td>string</td><td>Example: Alexandra Point</td></tr> <tr> <td>postalCode</td><td>string</td><td>Example: 159972</td></tr> </table>	block	string	Example: 323	streetName	string	Example: Alexandra Road	floorNumber	string	Example: 1	unitNumber	string	Example: 1232	buildingName	string	Example: Alexandra Point	postalCode	string	Example: 159972
block	string	Example: 323																		
streetName	string	Example: Alexandra Road																		
floorNumber	string	Example: 1																		
unitNumber	string	Example: 1232																		
buildingName	string	Example: Alexandra Point																		
postalCode	string	Example: 159972																		
contact	object	Contact numbers of the record, containing the following properties: <table border="1"> <tr> <td>primaryContactNo</td><td>string</td><td>Example: +65 6828 8888</td></tr> <tr> <td>secondaryContactNo</td><td>string</td><td>Example: +65 6828 8878</td></tr> <tr> <td>otherContactNo</td><td>string</td><td>Example: +65 6828 8868</td></tr> </table>	primaryContactNo	string	Example: +65 6828 8888	secondaryContactNo	string	Example: +65 6828 8878	otherContactNo	string	Example: +65 6828 8868									
primaryContactNo	string	Example: +65 6828 8888																		
secondaryContactNo	string	Example: +65 6828 8878																		
otherContactNo	string	Example: +65 6828 8868																		

thumbnails	array	<p>Image thumbnails to represent the record, each item is an object that may contain either of the following properties:</p> <table border="1"> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
images	array	<p>Images related to the record, each item is an object that may contain either of the following properties:</p> <table border="1"> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
documents	array	<p>Documents related to the record, each item is an object that may contain either of the following properties:</p> <table border="1"> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
videos	array	<p>Videos related to the record, each item is an object that may contain either of the following properties:</p> <table border="1"> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
officialWebsite	string	The official website of the record. Example: http://crazyelephant.sg/						
officialEmail	String	The official email of the record. Example: info@crazyelephant.sg						

businessHour	array	<p>Each item is an object describing the opening hour of the record, containing the following properties:</p> <table> <tr> <td>sequenceNumber</td><td>integer</td><td>Example: 1</td></tr> <tr> <td>day</td><td>string</td><td>Example: MON</td></tr> <tr> <td>daily</td><td>boolean</td><td>Example: false</td></tr> <tr> <td>openTime</td><td>string</td><td>Example: 10:30</td></tr> <tr> <td>closeTime</td><td>string</td><td>Example: 20:00</td></tr> <tr> <td>description</td><td>string</td><td>Example: close on public holidays</td></tr> </table> <p>Please refer to the examples in section <a href="#">1.2</a>.</p>	sequenceNumber	integer	Example: 1	day	string	Example: MON	daily	boolean	Example: false	openTime	string	Example: 10:30	closeTime	string	Example: 20:00	description	string	Example: close on public holidays
sequenceNumber	integer	Example: 1																		
day	string	Example: MON																		
daily	boolean	Example: false																		
openTime	string	Example: 10:30																		
closeTime	string	Example: 20:00																		
description	string	Example: close on public holidays																		
nearestMrtStation	string	<p>The nearest MRT Station to the record. Example: Clarke Quay MRT Station</p>																		
singaporeTourismAwards	string	<p>Field to declare if the record has been given an award. Example: Y N</p>																		
amenities	string	<p>Useful facilities found in the record. Example: Club Lounge</p>																		
supportedLanguage	string	<p>Supported language for this POI Example: en   zh-cn   zh-tw   ja   ko</p>																		

## 2.4. Cruises

The APIs listed below allow contribution of Cruises POIs and its details (e.g. sailing dates, cruise services). Cruise POIs can be retrieved by uuid or keyword search thereafter.

<div> <div>POST</div> <div> <b>createCruises</b>  <a href="https://tih-api.stb.gov.sg/content/v1/admin/cruises">https://tih-api.stb.gov.sg/content/v1/admin/cruises</a> </div> </div>		
Allows the creation of a Cruise POI. To create successfully, the following input parameters are mandatory: name, type, tags, description, body, terminal code, sailing date.		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Cruise to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "name": "3 NIGHT Port Klang &amp; Penang Cruise",   "description": "Enjoy a leisurely 4 nightly Port Klang &amp; Penang Cruise abroad the Queen of the Oceans!",   "body": "DAY 1 DEPARTS 17:00 \nWelcome Singapore, Singapore Singapore \nWelcome aboard Queen of the Oceans...",   "type": "Contemporary",   "tags": [     "Attractions"   ],   "contact": {     "primaryContactNo": "65454544",     "secondaryContactNo": "64654455",     "otherContactNo": ""   },   "organisationName": "Royal Caribbean International",   "officialEmail": "contactus@royalcaribbean.com",   "officialWebsite": "royalcaribbean.com",   "sailingDates": [     {       "startDate": "2019-08-01",       "endDate": "2019-08-04"     }   ],   "sailingItineraryURL": "",   "terminalCode": "MBCCS",   "cruiseServices": {     "flyCruise": "Yes", </pre>		

```

    "flyCruiseURL": "",
    "cruiseFly": "Yes",
    "cruiseFlyURL": ""
  }
  "amenities": "Business Centre,ATM",
  "leadInCabinRates": "S$101 - S$200",
  "thumbnails": [{
    "uuid": "", "url": "", "libraryUuid": ""
  }],
  "images": [{
    "uuid": "", "url": "", "libraryUuid": ""
  }],
  "videos": [{
    "uuid": "", "url": "", "libraryUuid": ""
  }],
  "documents": [{
    "uuid": "", "url": "", "libraryUuid": ""
  }]
}

```

**Notes:**

- terminalCode: pick either one of the cruise terminal available in Singapore: “MBCCS” (Marina Bay Cruise Centre Singapore) or “SCC” (Singapore Cruise Centre).
- sailingDates: include at least 1 sailing date that consists of “startDate” and “endDate”.

DELETE

deleteCruises

https://tih-api.stb.gov.sg/content/v1/admin/cruises/{uuid}

Allows the deletion of an existing Cruise POI through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchCruisesByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify a Cruise	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

```
{  
  "uuid": "0082f3218119c584b9d922cfd2ed2170ffa",  
  "language": "EN",  
}
```

PUT

updateCruises  
https://tih-api.stb.gov.sg/content/v1/admin/cruises/{uuid}

Allows an existing Cruise POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchCruisesByKeyword API.

REQUEST		
Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify a Cruise. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Cruise to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

body Example

```
{  "name": "3 NIGHT Port Klang & Penang Cruise",  "description": "Enjoy a leisurely 4 nightly Port Klang & Penang Cruise abroad the Queen of the Oceans!",  "body": "DAY 1 DEPARTS 17:00 \nWelcome Singapore, Singapore Singapore \nWelcome aboard Queen of the Oceans...",  "type": "Contemporary",  "tags": [    "Attractions"  ],  "contact": {    "primaryContactNo": "65454544",    "secondaryContactNo": "64654455",    "otherContactNo": ""  },  },  "organisationName": "Royal Caribbean International",  "officialEmail": "contactus@royalcaribbean.com",  "officialWebsite": "royalcaribbean.com",  "sailingDates": [    {      "startDate": "2019-08-01",      "endDate": "2019-08-04"    }  ],  },  "sailingItineraryURL": "",  "terminalCode": "MBCCS",  "cruiseServices": {    "flyCruise": "Yes",    "flyCruiseURL": "",    "cruiseFly": "Yes",
```

```
"cruiseFlyURL": ""
}
"amenities": "Business Centre,ATM",
"leadInCabinRates": "S$101 - S$200",
"thumbnails": [{
  "uuid":"", "url":"", "libraryUuid":""
}],
"images": [{
  "uuid":"", "url":"", "libraryUuid":""
}],
"videos": [{
  "uuid":"", "url":"", "libraryUuid":""
}],
"documents": [{
  "uuid":"", "url":"", "libraryUuid":""
}]
}
```

## 2.5. Events

The APIs listed below allow contribution of various Events POIs and its details (e.g. type, location, price) . Event POIs can be retrieved by uuid or keyword search thereafter.

<div> <div>POST</div> <div> <b>createEvent</b>  <a href="https://tih-api.stb.gov.sg/content/v1/admin/event">https://tih-api.stb.gov.sg/content/v1/admin/event</a> </div> </div>		
Allows the creation of an Event POI. To create successfully, the following input parameters are mandatory: name, type, tags, description and body.		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Event to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "uuid": "",   "name": "Grand Prix Season Singapore",   "type": "Sports",   "tags": ["Museums"],   "description": "Racing back with a bang, the Grand Prix Season Singapore (GPSS) is set to light up the city with a blockbuster lineup of festivities off and on the tracks.",   "contact": {     "primaryContactNo": "+65 6828 8888",     "secondaryContactNo": "",     "otherContactNo": ""   },   "location": {     "latitude": "1.287",     "longitude": "103.805"   },   "officialWebsite": "https://www.singaporegp.sg/",   "officialEmail": "info@singaporegp.sg",   "body": "Racing back with a bang, the Grand Prix Season Singapore (GPSS) is set to light up the city with a blockbuster lineup of festivities off and on the tracks. It's a bumper year of non-stop action. For fans of motorsports, the FORMULA 1 2018 SINGAPORE AIRLINES SINGAPORE GRAND PRIX (14-16Sep) is an epic showdown that's not to be missed. Spectators can expect to be blown away by adrenaline-pumping races under the stars against Singapore's glittering cityscape, with the crème-de-la-crème of race drivers competing for the coveted championship title.",   "thumbnails": [</pre>		



```
{
  "uuid": "",
  "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
}
],
"images": [
{
  "uuid": "",
  "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
}
],
"videos": [
{
  "uuid": "",
  "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
}
],
"eventOrganizer": "Singapore Tourism Board",
"address": {
  "block": "323",
  "streetName": "Alexandra Road",
  "floorNumber": "1",
  "unitNumber": "323",
  "buildingName": "Alexandra Point",
  "postalCode": "159972"
},
"nearestMrtStation": "Changi Airport MRT Station",
"price": "$100.00",
"ticketed": "Y",
"startDate": "2017-10-20T09:00:00Z",
"endDate": "2017-10-30T18:00:00Z",
"supportedLanguage": "en"
}
```

## POST

## createEventDetails

<https://tih-api.stb.gov.sg/content/v1/admin/event/{uuid}/detail>

Allows the creation of a sub-Event hosted by Main Event POI. To create successfully, the following input parameters are mandatory: name, type, tags, description and body. An Event record need to be created before creating 1/multiple sub-Event Details record(s). The uuid is the identifier for the main Event record.

### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify an event detail. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Event to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

### Example

```
{
  "uuid": "",
  "parentUuid": "004f74889a0baa14fe2a16ee22fb4b20b21",
  "name": "Porsche master class",
  "location": {
    "latitude": "1.287",
    "longitude": "103.805"
  },
  "address": {
    "block": "323",
    "streetName": "Alexandra Road",
    "floorNumber": "1",
    "unitNumber": "323",
    "buildingName": "Alexandra Point",
    "postalCode": "159972"
  },
  "timePeriod": [
    {
      "label": "string",
      "startDate": "2018-10-08T07:53:16.301Z",
      "endDate": "2018-10-08T07:53:16.301Z",
      "startTime": "string",
      "endTime": "string"
    }
  ],
  "supportedLanguage": "en"
}
```

**DELETE**

## deleteEvent

<https://tih-api.stb.gov.sg/content/v1/admin/event/{uuid}>

Allows the deletion of an existing Event POI through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchEventByKeyword API.

It is recommended that the related EventDetail record(s) is to be deleted.

### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify an event	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

### Example

```
{
  "uuid": "004f74889a0baa14fe2a16ee22fb4b20b21",
  "language": "EN",
}
```

**DELETE**

## deleteEventDetail

<https://tih-api.stb.gov.sg/content/v1/admin/event/{uuid}/detail/{uid}>

Allows the deletion of an existing sub-Event Detail through the use of a unique identifier. The acronym for the unique identifier is uid. This uid is created when you create an Event Detail. If you have not documented the uid, you can fetch it by using getEventDetailsByUuid API.

### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify an event details	Yes
parentuuid	Attribute used to uniquely identify the event parent	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

### Example

```
{
  "uuid": "004f74889a0baa14fe2a16ee22fb4b20b21",
  "parentuuid": "004f74889a0baa14fe2a16ee22fb4b20b21",
  "language": "EN",
}
```

PUT

updateEvent  
https://tih-api.stb.gov.sg/content/v1/admin/event/{uuid}

Allows an existing Event POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchEventByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify an event. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Event to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

```
{  "uuid": " 004f74889a0baa14fe2a16ee22fb4b20b21",  "name": "Grand Prix Season Singapore",  "type": "Entertainment",  "tags": ["Museums"],  "description": "Racing back with a bang, the Grand Prix Season Singapore (GPSS) is set to light up the city with a blockbuster lineup of festivities off and on the tracks.",  "contact": {    "primaryContactNo": "+65 6828 8888",    "secondaryContactNo": "",    "otherContactNo": ""  },  "location": {    "latitude": "1.287",    "longitude": "103.805"  },  "officialWebsite": "https://www.singaporegp.sg/",  "officialEmail": "info@singaporegp.sg",  "body": "Racing back with a bang, the Grand Prix Season Singapore (GPSS) is set to light up the city with a blockbuster lineup of festivities off and on the tracks. It's a bumper year of non-stop action. For fans of motorsports, the FORMULA 1 2018 SINGAPORE AIRLINES SINGAPORE GRAND PRIX (14-16Sep) is an epic showdown that's not to be missed. Spectators can expect to be blown away by adrenaline-pumping races under the stars against Singapore's glittering cityscape, with the crème-de-la-crème of race drivers competing for the coveted championship title.",  "thumbnails": [    {      "uuid": "",
```

```
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
"images": [
  {
    "uuid": "",
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
"videos": [
  {
    "uuid": "",
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
"eventOrganizer": "Singapore Tourism Board",
"address": {
  "block": "323",
  "streetName": "Alexandra Road",
  "floorNumber": "1",
  "unitNumber": "323",
  "buildingName": "Alexandra Point",
  "postalCode": "159972"
},
"nearestMrtStation": "Changi Airport MRT Station",
"price": "$100.00",
"ticketed": "Y",
"startDate": "2017-10-20T09:00:00Z",
"endDate": "2017-10-30T18:00:00Z",
"supportedLanguage": "en"
}
```

PUT

updateEventDetails  
https://tih-api.stb.gov.sg/content/v1/admin/event/{uuid}/detail/{uid}

Allows an existing Event POI details to be updated through the use of a unique identifier. The acronym for the unique identifier is uid. This uid is created when you create an event detail. If you have not documented the uid, you can fetch it by using getEventDetailsByUuid API.

REQUEST

Parameters	Description	Mandatory
uid	Attribute used to uniquely identify an event details	Yes
uuid	Attribute used to uniquely identify the event parent	Yes
body	JSON which holds all the properties of the Event Details to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

```
{  "uuid": "004f74889a0baa14fe2a16ee22fb4b20b21",  "parentuuid": "004f74889a0baa14fe2a16ee22fb4b20b21",  "name": "",  "location": {    "latitude": "1.287",    "longitude": "103.805"  },  "address": {    "block": "323",    "streetName": "Alexandra Road",    "floorNumber": "1",    "unitNumber": "323",    "buildingName": "Alexandra Point",    "postalCode": "159972"  },  "timePeriod": [    {      "label": "string",      "startDate": "2018-10-08T07:53:16.301Z",      "endDate": "2018-10-08T07:53:16.301Z",      "startTime": "string",      "endTime": "string"    }  ]}
```

## Event Data Schema:

Parameter Name	Parameter Type	Parameter Description																		
uuid	string	Attribute used to uniquely identify an record. Example: 00290ed83551389471abe25eecf4ddb9563																		
name	string	Name of the record. Example: Grand Prix Season Singapore																		
type	string	Type in which the record belongs to. Example: Arts Attractions Entertainment Food & Beverages History & Culture MICE Nature & Wildlife Shopping Sports Others																		
tags	array	Tags pertaining to the record, each item is a string. Example: [Entertainment]																		
description	string	Field to describe the record Example: Racing back with a bang, the Grand Prix Season Singapore (GPSS) is set to light up the city with a blockbuster lineup of festivities off and on the tracks.																		
body	string	Content body of the record Example: Racing back with a bang, the Grand Prix Season Singapore (GPSS) is set to ...																		
location	object	Location of the record, containing the following properties: <table border="1"> <tr> <td>latitude</td><td>string</td><td>Example: 1.287</td></tr> <tr> <td>longitude</td><td>String</td><td>Example: 103.805</td></tr> </table>	latitude	string	Example: 1.287	longitude	String	Example: 103.805												
latitude	string	Example: 1.287																		
longitude	String	Example: 103.805																		
address	object	Structured address of the record, containing the following properties: <table border="1"> <tr> <td>block</td><td>string</td><td>Example: 323</td></tr> <tr> <td>streetName</td><td>string</td><td>Example: Alexandra Road</td></tr> <tr> <td>floorNumber</td><td>string</td><td>Example: 1</td></tr> <tr> <td>unitNumber</td><td>string</td><td>Example: 1232</td></tr> <tr> <td>buildingName</td><td>string</td><td>Example: Alexandra Point</td></tr> <tr> <td>postalCode</td><td>string</td><td>Example: 159972</td></tr> </table>	block	string	Example: 323	streetName	string	Example: Alexandra Road	floorNumber	string	Example: 1	unitNumber	string	Example: 1232	buildingName	string	Example: Alexandra Point	postalCode	string	Example: 159972
block	string	Example: 323																		
streetName	string	Example: Alexandra Road																		
floorNumber	string	Example: 1																		
unitNumber	string	Example: 1232																		
buildingName	string	Example: Alexandra Point																		
postalCode	string	Example: 159972																		
contact	object	Contact numbers of the record, containing the following properties: <table border="1"> <tr> <td>primaryContactNo</td><td>string</td><td>Example: +65 6828 8888</td></tr> <tr> <td>secondaryContactNo</td><td>string</td><td>Example: +65 6828 8878</td></tr> <tr> <td>otherContactNo</td><td>string</td><td>Example: +65 6828 8868</td></tr> </table>	primaryContactNo	string	Example: +65 6828 8888	secondaryContactNo	string	Example: +65 6828 8878	otherContactNo	string	Example: +65 6828 8868									
primaryContactNo	string	Example: +65 6828 8888																		
secondaryContactNo	string	Example: +65 6828 8878																		
otherContactNo	string	Example: +65 6828 8868																		

thumbnails	array	<p>Image thumbnails to represent the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
images	array	<p>Images related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
documents	array	<p>Documents related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
videos	array	<p>Videos related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
officialWebsite	string	The official website of the record. Example: <a href="https://www.singaporegp.sg/">https://www.singaporegp.sg/</a>						
officialEmail	string	The official email of the record. Example: <a href="mailto:info@singaporegp.sg">info@singaporegp.sg</a>						



eventOrganizer	string	Attribute used to indicate the Event organiser. Example: Singapore Tourism Board
ticketed	string	Field to declare if the event admission is ticketed. Example: Y N
price	string	Event admission price. Example : \$100.00
startDate	date-time	Event start date. Example : 2017-10-20T09:00:00Z
endDate	date-time	Event end date Example: 2017-10-30T18:00:00Z
nearestMrtStation	string	The nearest MRT Station to the record. Example: Clarke Quay MRT Station
singaporeTourismAwards	string	Field to declare if the record has been given an award. Example: Y N
supportedLanguage	string	Supported language for this POI Example: en   zh-cn   zh-tw   ja   ko

## 2.6. Food and Beverages

The APIs listed below allow contribution of various Food and Beverages Content and its details (e.g. type, amenities, business hours) . Food and Beverages POIs can be retrieved by uuid or keyword search thereafter.

<div> <div>POST</div> <div> <b>createFoodBeverages</b>  <a href="https://tih-api.stb.gov.sg/content/v1/admin/food-beverages">https://tih-api.stb.gov.sg/content/v1/admin/food-beverages</a> </div> </div>		
Allows the creation of a Food and Beverage POI. To create successfully, the following input parameters are mandatory: name, type, tags, description and body.		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Food and Beverage establishments to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "uuid": "",   "name": "Jumbo Seafood Restaurant",   "type": "Restaurants",   "location": {     "latitude": "1.287",     "longitude": "103.805"   },   "address": {     "block": "323",     "streetName": "Alexandra Road",     "floorNumber": "1",     "unitNumber": "323",     "buildingName": "Alexandra Point",     "postalCode": "159972"   },   "thumbnails": [     {       "uuid": "",       "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"     }   ],   "images": [     {       "uuid": "",</pre>		

```

    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
"documents": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
"cuisine": "Local",
"contact": {
  "primaryContactNo": "+65 6828 8888",
  "secondaryContactNo": "",
  "otherContactNo": ""
},
"businessHour": [
  {
    "day": "daily",
    "openTime": "00:00",
    "closeTime": "23:59",
    "description": "",
    "sequenceNumber": 1,
    "daily": true
  }
],
"notes": "",
"nearestMrtStation": "Clarke Quay MRT Station",
"officialWebsite": "https://www.jumboseafood.com.sg/en/home",
"officialEmail": "info@jumbo.sg",
"body": "Jumbo Seafood is a well-known local seafood restaurant in Singapore
that serves live seafood and local specialities.",
"videos": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
"amenities": "Central",
"supportedLanguage": "en"
}

```

**DELETE**

## deleteFoodBeverages

<https://tih-api.stb.gov.sg/content/v1/admin/food-beverages/{uuid}>

Allows the deletion of an existing Food & Beverages POI through the use of a unique identifier. The acronym for unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchFoodBeveragesByKeyword API.

### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify Food and Beverages	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

### Example

```
{
  "uuid": "003928a476f113c4f6d89d5206714d50fc5",
  "language": "EN",
}
```

**PUT**

## updateFoodBeverages

<https://tih-api.stb.gov.sg/content/v1/admin/food-beverages/{uuid}>

Allows an existing Food & Beverages POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchFoodBeveragesByKeyword API.

### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify Food and Beverages. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Food and Beverage establishments to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] The preset value EN will be applied by default if no other languages are selected.	No

### Example

```
{
  "uuid": "003928a476f113c4f6d89d5206714d50fc5",
  "name": "Jumbo Seafood Restaurant",
  "type": "Restaurants",
  "location": {
```

```

    "latitude": "1.287",
    "longitude": "103.805"
  },
  "address": {
    "block": "323",
    "streetName": "Alexandra Road",
    "floorNumber": "1",
    "unitNumber": "323",
    "buildingName": "Alexandra Point",
    "postalCode": "159972"
  },
  "thumbnails": [
    {
      "uuid": "",
      "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
    }
  ],
  "images": [
    {
      "uuid": "",
      "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
    }
  ],
  "documents": [
    {
      "uuid": "",
      "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
    }
  ],
  "cuisine": "Local",
  "contact": {
    "primaryContactNo": "+65 6828 8888",
    "secondaryContactNo": "",
    "otherContactNo": ""
  },
  "businessHour": [
    {
      "day": "daily",
      "openTime": "00:00",
      "closeTime": "23:59",
      "description": "",
      "sequenceNumber": 1,
      "daily": true
    }
  ]
}

```

```
],
  "notes": "",
  "nearestMrtStation": "Clarke Quay MRT Station",
  "officialWebsite": "https://www.jumboseafood.com.sg/en/home",
  "officialEmail": "info@jumbo.sg",
  "body": "Jumbo Seafood is a well-known local seafood restaurant in Singapore that serves live seafood and local specialities.",
  "videos": [
    {
      "uuid": "",
      "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
    }
  ],
  "amenities": "Central",
  "supportedLanguage": "en"
}
```

## Food & Beverage Data Schema:

Parameter Name	Parameter Type	Parameter Description																		
uuid	string	Attribute used to uniquely identify an record. Example: 00290ed83551389471abe25eecf4ddb9563																		
name	string	Name of the record. Example: Jumbo Seafood Restaurant																		
type	string	Type in which the record belongs to. Example: Cafés  Hawker Centres  Restaurants  Others																		
tags	array	Tags pertaining to the record, each item is a string. Example: [Central]																		
description	string	Field to describe the record Example: Jumbo Seafood is a well-known local seafood restaurant in Singapore that serves live seafood and local specialities.																		
body	string	Content body of the record Example: Jumbo Seafood is a well-known local seafood restaurant in Singapore that serves live seafood and local specialities ...																		
location	object	Location of the record, containing the following properties: <table border="1"> <tr> <td>latitude</td><td>string</td><td>Example: 1.287</td></tr> <tr> <td>longitude</td><td>String</td><td>Example: 103.805</td></tr> </table>	latitude	string	Example: 1.287	longitude	String	Example: 103.805												
latitude	string	Example: 1.287																		
longitude	String	Example: 103.805																		
address	object	Structured address of the record, containing the following properties: <table border="1"> <tr> <td>block</td><td>string</td><td>Example: 323</td></tr> <tr> <td>streetName</td><td>string</td><td>Example: Alexandra Road</td></tr> <tr> <td>floorNumber</td><td>string</td><td>Example: 1</td></tr> <tr> <td>unitNumber</td><td>string</td><td>Example: 1232</td></tr> <tr> <td>buildingName</td><td>string</td><td>Example: Alexandra Point</td></tr> <tr> <td>postalCode</td><td>string</td><td>Example: 159972</td></tr> </table>	block	string	Example: 323	streetName	string	Example: Alexandra Road	floorNumber	string	Example: 1	unitNumber	string	Example: 1232	buildingName	string	Example: Alexandra Point	postalCode	string	Example: 159972
block	string	Example: 323																		
streetName	string	Example: Alexandra Road																		
floorNumber	string	Example: 1																		
unitNumber	string	Example: 1232																		
buildingName	string	Example: Alexandra Point																		
postalCode	string	Example: 159972																		
contact	object	Contact numbers of the record, containing the following properties: <table border="1"> <tr> <td>primaryContactNo</td><td>string</td><td>Example: +65 6828 8888</td></tr> <tr> <td>secondaryContactNo</td><td>string</td><td>Example: +65 6828 8878</td></tr> <tr> <td>otherContactNo</td><td>string</td><td>Example: +65 6828 8868</td></tr> </table>	primaryContactNo	string	Example: +65 6828 8888	secondaryContactNo	string	Example: +65 6828 8878	otherContactNo	string	Example: +65 6828 8868									
primaryContactNo	string	Example: +65 6828 8888																		
secondaryContactNo	string	Example: +65 6828 8878																		
otherContactNo	string	Example: +65 6828 8868																		

thumbnails	array	<p>Image thumbnails to represent the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
images	array	<p>Images related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
documents	array	<p>Documents related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
videos	array	<p>Videos related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
officialWebsite	string	<p>The official website of the record. Example: <a href="https://www.jumboseafood.com.sg/en/home">https://www.jumboseafood.com.sg/en/home</a></p>						
officialEmail	String	<p>The official email of the record. Example: info@jumbo.sg</p>						



businessHour	array	<p>Each item is an object describing the opening hour of the record, containing the following properties:</p> <table border="1"> <tr> <td>sequenceNumber</td><td>integer</td><td>Example: 1</td></tr> <tr> <td>day</td><td>string</td><td>Example: MON</td></tr> <tr> <td>daily</td><td>boolean</td><td>Example: false</td></tr> <tr> <td>openTime</td><td>string</td><td>Example: 10:30</td></tr> <tr> <td>closeTime</td><td>string</td><td>Example: 20:00</td></tr> <tr> <td>description</td><td>string</td><td>Example: close on public holidays</td></tr> </table> <p>Please refer to the examples in section <a href="#">1.2</a>.</p>	sequenceNumber	integer	Example: 1	day	string	Example: MON	daily	boolean	Example: false	openTime	string	Example: 10:30	closeTime	string	Example: 20:00	description	string	Example: close on public holidays
sequenceNumber	integer	Example: 1																		
day	string	Example: MON																		
daily	boolean	Example: false																		
openTime	string	Example: 10:30																		
closeTime	string	Example: 20:00																		
description	string	Example: close on public holidays																		
cuisine	string	Cuisine type being served in the establishment. Example: Local																		
nearestMrtStation	string	The nearest MRT Station to the record. Example: Clarke Quay MRT Station																		
singaporeTourismAwards	string	Field to declare if the record has been given an award. Example: Y N																		
amenities	string	Useful facilities found in the record. Example: Wheelchair Accessible																		
supportedLanguage	string	Supported language for this POI Example: en   zh-cn   zh-tw   ja   ko																		

## 2.7. Malls and Shops

The APIs listed below allow contribution of Malls and Shops POIs and its details (e.g. type, amenities, business hours) . Malls and Shops POIs can be retrieved by uuid or keyword search thereafter.

POST <b>createShops</b> <a href="https://tih-api.stb.gov.sg/content/v1/admin/shops">https://tih-api.stb.gov.sg/content/v1/admin/shops</a>		
Allows the creation of a Mall or Shop POI. To create successfully, the following input parameters are mandatory: name, type, tags, description and body.		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Malls and Shops to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "uuid": "",   "name": "Bras Basah Complex",   "type": "Malls",   "tags": ["Bras Basah"],   "description": "Bras Basah Complex is a cultural feast that is full of books, art, music and literature. Just across the road from the famous Raffles Hotel, the complex has a large selection of fiction, children's books and magazines.",   "location": {     "latitude": "1.287",     "longitude": "103.805"   },   "address": {     "block": "323",     "streetName": "Alexandra Road",     "floorNumber": "1",     "unitNumber": "323",     "buildingName": "Alexandra Point",     "postalCode": "159972"   },   "thumbnails": [     {       "uuid": "",       "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"     }   ] }</pre>		

```

    }
  ],
  "images": [
    {
      "uuid": "",
      "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
    }
  ],
  "documents": [
    {
      "uuid": "",
      "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
    }
  ],
  "contact": {
    "primaryContactNo": "+65 6828 8888",
    "secondaryContactNo": "",
    "otherContactNo": ""
  },
  "businessHour": [
    {
      "day": "daily",
      "openTime": "00:00",
      "closeTime": "23:59",
      "description": "",
      "sequenceNumber": 1,
      "daily": true
    }
  ],
  "notes": "",
  "nearestMrtStation": "Bras Basah MRT Station",
  "officialWebsite": "http://www.bras-basah-complex.com.sg/bbc/",
  "body": "Bras Basah Complex is a cultural feast that is full of books, art, music and literature. Just across the road from the famous Raffles Hotel, the complex has a large selection of fiction, children's books and magazines.",
  "videos": [
    {
      "uuid": "",
      "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
    }
  ],
  "amenities": "Children's Club",
  "supportedLanguage": "en"
}

```

DELETE

deleteShops

https://tih-api.stb.gov.sg/content/v1/admin/shops/{uuid}

Allows the deletion of an existing Mall or Shop POI through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchShopsByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify shops.	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

```
{
  "uuid": "007b61fd0721238440db5d4df1c523036f4",
  "language": "EN",
}
```

PUT

updateShops  
https://tih-api.stb.gov.sg/content/v1/admin/shops/{uuid}

Allows an existing Mall or Shop POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchShopsByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify Shops. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Malls and Shops to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

```
{  "uuid": "007b61fd0721238440db5d4df1c523036f4",  "name": "Bras Basah Complex",  "type": "Bazaars & Flea Markets|Boutiques|Department Stores|Malls|Others",  "tags": ["Bras Basah"],}
```

```

"description": "Bras Basah Complex is a cultural feast that is full of
books, art, music and literature. Just across the road from the famous Raffles
Hotel, the complex has a large selection of fiction, children's books and
magazines.",
"location": {
  "latitude": "1.287",
  "longitude": "103.805"
},
"address": {
  "block": "323",
  "streetName": "Alexandra Road",
  "floorNumber": "1",
  "unitNumber": "323",
  "buildingName": "Alexandra Point",
  "postalCode": "159972"
},
"thumbnails": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
"images": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
"documents": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
"contact": {
  "primaryContactNo": "+65 6828 8888",
  "secondaryContactNo": "",
  "otherContactNo": ""
},
"businessHour": [
  {
    "day": "daily",
    "openTime": "00:00",
    "closeTime": "23:59",

```

```
    "description": "",
    "sequenceNumber": 1,
    "daily": true
  }
],
"nearestMrtStation": "Bras Basah MRT Station",
"officialWebsite": "http://www.bras-basah-complex.com.sg/bbc/",
"body": "Bras Basah Complex is a cultural feast that is full of books, art, music and literature. Just across the road from the famous Raffles Hotel, the complex has a large selection of fiction, children's books and magazines.",
"videos": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
"amenities": "Children's Club",
"supportedLanguage": "en"
}
```

## Mall & Shop Data Schema:

Parameter Name	Parameter Type	Parameter Description																		
uuid	string	Attribute used to uniquely identify an record. Example: 00290ed83551389471abe25eecf4ddb9563																		
name	string	Name of the record. Example: Bras Basah Complex																		
type	string	Type in which the record belongs to. Example: Bazaars & Flea Markets  Boutiques  Department Stores  Malls  Others																		
tags	array	Tags pertaining to the record, each item is a string. Example: [Bras Basah]																		
description	string	Field to describe the record Example: Bras Basah Complex is a cultural feast that is full of books, art, music and literature. Just across the road from the famous Raffles Hotel, the complex has a large selection of fiction, children's books and magazines.																		
body	string	Content body of the record Example: Bras Basah Complex is a cultural feast that is full of books, art, music and literature. Just across the road ...																		
location	object	Location of the record, containing the following properties: <table border="1"> <tr> <td>latitude</td><td>string</td><td>Example: 1.287</td></tr> <tr> <td>longitude</td><td>String</td><td>Example: 103.805</td></tr> </table>	latitude	string	Example: 1.287	longitude	String	Example: 103.805												
latitude	string	Example: 1.287																		
longitude	String	Example: 103.805																		
address	object	Structured address of the record, containing the following properties: <table border="1"> <tr> <td>block</td><td>string</td><td>Example: 323</td></tr> <tr> <td>streetName</td><td>string</td><td>Example: Alexandra Road</td></tr> <tr> <td>floorNumber</td><td>string</td><td>Example: 1</td></tr> <tr> <td>unitNumber</td><td>string</td><td>Example: 1232</td></tr> <tr> <td>buildingName</td><td>string</td><td>Example: Alexandra Point</td></tr> <tr> <td>postalCode</td><td>string</td><td>Example: 159972</td></tr> </table>	block	string	Example: 323	streetName	string	Example: Alexandra Road	floorNumber	string	Example: 1	unitNumber	string	Example: 1232	buildingName	string	Example: Alexandra Point	postalCode	string	Example: 159972
block	string	Example: 323																		
streetName	string	Example: Alexandra Road																		
floorNumber	string	Example: 1																		
unitNumber	string	Example: 1232																		
buildingName	string	Example: Alexandra Point																		
postalCode	string	Example: 159972																		
contact	object	Contact numbers of the record, containing the following properties: <table border="1"> <tr> <td>primaryContactNo</td><td>string</td><td>Example: +65 6828 8888</td></tr> <tr> <td>secondaryContactNo</td><td>string</td><td>Example: +65 6828 8878</td></tr> <tr> <td>otherContactNo</td><td>string</td><td>Example: +65 6828 8868</td></tr> </table>	primaryContactNo	string	Example: +65 6828 8888	secondaryContactNo	string	Example: +65 6828 8878	otherContactNo	string	Example: +65 6828 8868									
primaryContactNo	string	Example: +65 6828 8888																		
secondaryContactNo	string	Example: +65 6828 8878																		
otherContactNo	string	Example: +65 6828 8868																		

thumbnails	array	<p>Image thumbnails to represent the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
images	array	<p>Images related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
documents	array	<p>Documents related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
videos	array	<p>Videos related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
officialWebsite	string	The official website of the record. Example: http://www.bras-basah-complex.com.sg/bbc/						
officialEmail	String	The official email of the record. Example: info@bras-basah-complex.com.sg						



businessHour	array	<p>Each item is an object describing the opening hour of the record, containing the following properties:</p> <table> <tr> <td>sequenceNumber</td><td>integer</td><td>Example: 1</td></tr> <tr> <td>day</td><td>string</td><td>Example: MON</td></tr> <tr> <td>daily</td><td>boolean</td><td>Example: false</td></tr> <tr> <td>openTime</td><td>string</td><td>Example: 10:30</td></tr> <tr> <td>closeTime</td><td>string</td><td>Example: 20:00</td></tr> <tr> <td>description</td><td>string</td><td>Example: close on public holidays</td></tr> </table> <p>Please refer to the examples in section <a href="#">1.2</a>.</p>	sequenceNumber	integer	Example: 1	day	string	Example: MON	daily	boolean	Example: false	openTime	string	Example: 10:30	closeTime	string	Example: 20:00	description	string	Example: close on public holidays
sequenceNumber	integer	Example: 1																		
day	string	Example: MON																		
daily	boolean	Example: false																		
openTime	string	Example: 10:30																		
closeTime	string	Example: 20:00																		
description	string	Example: close on public holidays																		
nearestMrtStation	string	<p>The nearest MRT Station to the record. Example: Bras Basah MRT Station</p>																		
singaporeTourismAwards	string	<p>Field to declare if the record has been given an award. Example: Y N</p>																		
amenities	string	<p>Useful facilities found in the record. Example: Children's Club</p>																		
supportedLanguage	string	<p>Supported language for this POI Example: en   zh-cn   zh-tw   ja   ko</p>																		

## 2.8. Precincts

The APIs listed below allow contribution of Precincts POIs and its details (e.g. recommended dwell time, featured POIs). Precincts POIs can be retrieved by uuid or keyword search thereafter.

POST <b>createPrecincts</b> <a href="https://tih-api.stb.gov.sg/content/v1/admin/precincts">https://tih-api.stb.gov.sg/content/v1/admin/precincts</a>		
Allows the creation of a Precinct POI. To create successfully, the following input parameters are mandatory: name, tags, description, body, organisation name, perimeter, and recommended dwell time (in hours).		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Precinct to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "uuid": "",   "name": "Chinatown",   "categoryDescription": "Precincts",   "description": "Chinatown is Singapore's traditional Chinese quarter where you will find an eclectic mix of traditional...",   "body": "A walk down Chinatown's narrow streets with their picturesque shophouses ...",   "tags": ["Heartlands"],   "organisationName": "Chinatown Association",   "contact": {     "primaryContactNo": "",     "secondaryContactNo": "",     "otherContactNo": ""   },   "officialEmail": "help@chinatown.sg",   "officialWebsite": "chinatown.sg",   "thumbnails": [ {"uuid": "", "url": ""} ],   "images": [ {"uuid": "", "url": ""} ],   "videos": [ {"uuid": "", "url": ""} ],   "documents": [ {"uuid": "", "url": ""} ],   "perimeter": [     [{"lon": 103.852416203678, "lat": 1.29381174228598}, {"lon": 103.852590829901, "lat": 1.29444064327385}, ...]   ],   "recommendedDwellTime": 5,   "nearestMrtStation": "Chinatown", }</pre>		

```

"featuredPOI": [ "10168fc9bf8091f4a4186baeec2f71c3c52",
"00788cd874014164f9e82247b112c0a5dd9",
"101fd529ef999964f66bf9283a06b266a26", "...", "..."],

"supportedLanguage": [ "EN"],
}

```

**Notes:**

- featuredPOI: up to 5 POIs unique identifier (uuid) that can be listed as featured POIs within the precinct
- recommendedDwellTime: recommended number of hours needed to explore the precinct within a day

<b>DELETE</b>	<b>deletePrecinct</b> <a href="https://tih-api.stb.gov.sg/content/v1/admin/precincts/{uuid}" style="color: white;">https://tih-api.stb.gov.sg/content/v1/admin/precincts/{uuid}</a>	
	<p>Allows the deletion of an existing Precinct POI through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchPrecinctsByKeyword API.</p>	
<b>REQUEST</b>		
<b>Parameters</b>	<b>Description</b>	<b>Mandatory</b>
uuid	Attribute used to uniquely identify a Precinct	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
<b>Example</b>		
<pre> {   "uuid": "0082f3218119c584b9d922cfd2ed2170ffa",   "language": "EN", } </pre>		

PUT

updatePrecincts  
https://tih-api.stb.gov.sg/content/v1/admin/Precincts/{uuid}

Allows an existing Precinct POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchPrecinctsByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify a Precinct. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Precinct to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

body Example

```
{  "uuid": "101de0f076e7be34b5aa7d37bb5ac532ce2",  "name": "Chinatown",  "categoryDescription": "Precincts",  "description": "Chinatown is Singapore's traditional Chinese quarter where you will find an eclectic mix of traditional...",  "body": "A walk down Chinatown's narrow streets with their picturesque shophouses ...",  "tags": ["Heartlands"],  "organisationName": "Chinatown Association"  "contact": {    "primaryContactNo": "",    "secondaryContactNo": "",    "otherContactNo": ""  },  "officialEmail": "help@chinatown.sg",  "officialWebsite": "chinatown.sg",  "thumbnails": [ {"uuid": "", "url":""} ]  "images": [ {"uuid": "", "url":""} ]  "videos": [ {"uuid": "", "url":""} ]  "documents": [ {"uuid": "", "url":""} ]  "perimeter": [{"lon":103.852416203678,"lat":1.29381174228598},{lon":103.852590829901,"lat":1.29444064327385},...]  "recommendedDwellTime": 5,  "nearestMrtStation": "Chinatown",  "featuredPOI":["", "", "", "", ""],  "supportedLanguage": ["EN"],  "companyDisplayName": "Singapore Tourism Board",  "metadata": {
```

```
    "createdDate": "2017-10-07T15:20:00Z",  
    "updatedAt": "2017-10-07T15:20:00Z",  
  }  
}
```

## Precinct Data Schema:

Parameter Name	Parameter Type	Parameter Description									
uuid	string	Attribute used to uniquely identify an record. Example: 00290ed83551389471abe25eecf4ddb9563									
name	string	Name of the record. Example: Orchard Road									
tags	array	Tags pertaining to the record, each item is a string. Example: [Shopping, Central]									
description	string	Field to describe the record Example: Singapore's most famous shopping precinct is home to a wealth of experiences.									
body	string	Content body of the record Example: Orchard Road's bustling boulevard is now a retail and dining paradise, with over 5,000 establishments offering the ultimate lifestyle experience to tourists and locals alike ...									
contact	object	Contact numbers of the record, containing the following properties: <table border="1"> <tr> <td>primaryContactNo</td><td>string</td><td>Example: +65 6828 8888</td></tr> <tr> <td>secondaryContactNo</td><td>string</td><td>Example: +65 6828 8878</td></tr> <tr> <td>otherContactNo</td><td>string</td><td>Example: +65 6828 8868</td></tr> </table>	primaryContactNo	string	Example: +65 6828 8888	secondaryContactNo	string	Example: +65 6828 8878	otherContactNo	string	Example: +65 6828 8868
primaryContactNo	string	Example: +65 6828 8888									
secondaryContactNo	string	Example: +65 6828 8878									
otherContactNo	string	Example: +65 6828 8868									
thumbnails	array	Image thumbnails to represent the record, each item is an object that may contain either of the following properties: <table border="1"> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>			
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563									
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>									
images	array	Images related to the record, each item is an object that may contain either of the following properties: <table border="1"> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>			
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563									
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>									

documents	array	<p>Documents related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
videos	array	<p>Videos related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
organizationName	string	The organization name the record belongs to. Example: Singapore Tourism Board						
officialWebsite	string	The official website of the record. Example: <a href="https://www.visitsingapore.com/see-do-singapore/places-to-see/orchard/">https://www.visitsingapore.com/see-do-singapore/places-to-see/orchard/</a>						
officialEmail	string	The official email of the record. Example: info@stb.gov.sg						
perimeter	array	<p>List of coordinates (latitude and longitude) that define the precinct boundary. Each coordinate is an object that contain the following properties:</p> <table> <tr> <td>lat</td><td>double</td><td>Example: 1.287</td></tr> <tr> <td>lon</td><td>double</td><td>Example: 103.805</td></tr> </table>	lat	double	Example: 1.287	lon	double	Example: 103.805
lat	double	Example: 1.287						
lon	double	Example: 103.805						
recommendedDwellTime	integer	Recommended dwell time per day (in hours). Example: 4						
nearestMrtStation	string	The nearest MRT Station to the record. Example: Orchard MRT Station						
featuredPOI	array	<p>List of the unique identifier (uuid) of the featured POIs within the precinct (up to 5 POIs). Example: ['00788cd874014164f9e82247b112c0a5dd9',</p>						

---

		'0012711da06fb094cb6841831bf36725d17', '001723e4c12dcfe43508f326dfd03f90895']
supportedLanguage	string	Supported language for this POI Example: en   zh-cn   zh-tw   ja   ko



## 2.9. Tours

The APIs listed below allow contribution of Tours POIs and its details (e.g. type, major stops, tour operating hours). Tour POIs can be retrieved by uuid or keyword search thereafter.

<div> <div>POST</div> <div> <b>createTour</b>  <a href="https://tih-api.stb.gov.sg/content/v1/admin/tour">https://tih-api.stb.gov.sg/content/v1/admin/tour</a> </div> </div>		
Allows the creation of a Tour POI. To create successfully, the following input parameters are mandatory: name, type, tags, description and body.		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Tour to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "uuid": "",   "name": "Outdoor Gardens Cruiser Tour",   "type": "Sightseeing",   "tags": ["Marina Bay"],   "description": "Visitors go on an audio-guided tour while travelling on a tram around the green oasis of Gardens by the Bay.",   "frequencyOfTours": "Every Monday, Wednesday, Friday",   "language": "English",   "tourDuration": "4 hours",   "thumbnails": [     {       "uuid": "",       "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"     }   ],   "images": [     {       "uuid": "",       "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"     }   ],   "documents": [     {</pre>		

```

    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
  "contact": {
    "primaryContactNo": "+65 6828 8888",
    "secondaryContactNo": "",
    "otherContactNo": ""
  },
  "officialWebsite": "http://www.gardensbythebay.com.sg/en/plan-your-
visit/tours-and-trails/outdoor-garden-cruiser-tours.html",
  "email": "feedback@gardensbythebay.com.sg",
  "body": "The breathtaking and eco-friendly Gardens by the Bay is an ideal
destination to spend a few quiet moments in the middle of Singapore's bustling
city centre. Visitors can enjoy a 25-minute ride on the Garden Cruiser tram
around the cooled conservatories, themed gardens and Supertree Grove. The tour
includes an audio commentary.",
  "videos": [
    {
      "uuid": "",
      "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
    }
  ],
  "price": "$100.00",
  "location": {
    "latitude": "1.287",
    "longitude": "103.805"
  },
  "startingPoint": "Hotel Pickup",
  "endingPoint": "Hotel Pickup",
  "tourOperatingHours": "9am - 1pm",
  "nearestMRTStation": "Bayfront MRT Station",
  "wheelChairFriendly": "Y",
  "childFriendly": "Y",
  "minimumAge": "12",
  "companyName": "Tour East Singapore",
  "majorStops": "Star Vista",
  "startDate": "2018-10-08T06:55:17.830Z",
  "endDate": "2018-10-08T06:55:17.830Z",
  "supportedLanguage": "en"
}

```

**DELETE**

## deleteTour

<https://tih-api.stb.gov.sg/content/v1/admin/tour/{uuid}>

Allows the deletion of an existing Tour POI through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchTourByKeyword API.

### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify Tours.	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

### Example

```
{
  "uuid": "0139c0cf40b822a4ec9ab5bd2a793dd61c2",
  "language": "EN",
}
```

**PUT**

## updateTour

<https://tih-api.stb.gov.sg/content/v1/admin/tour/{uuid}>

Allows an existing Tour POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchTourByKeyword API.

### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify a Tour. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Tour to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

### Example

```
{
  "uuid": "0139c0cf40b822a4ec9ab5bd2a793dd61c2",
  "name": "Outdoor Gardens Cruiser Tour",
  "type": "Sightseeing",
  "tags": ["Marina Bay"],
  "description": "Visitors go on an audio-guided tour while travelling on a tram around the green oasis of Gardens by the Bay.",
}
```

```

"frequencyOfTours": "Every Monday, Wednesday, Friday",
"language": "English",
"tourDuration": "4 hours",
"thumbnails": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
"images": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
"documents": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
"contact": {
  "primaryContactNo": "+65 6828 8888",
  "secondaryContactNo": "",
  "otherContactNo": ""
},
"officialWebsite": "http://www.gardensbythebay.com.sg/en/plan-your-visit/tours-and-trails/outdoor-garden-cruiser-tours.html",
"email": "feedback@gardensbythebay.com.sg",
"body": "The breathtaking and eco-friendly Gardens by the Bay is an ideal destination to spend a few quiet moments in the middle of Singapore's bustling city centre. Visitors can enjoy a 25-minute ride on the Garden Cruiser tram around the cooled conservatories, themed gardens and Supertree Grove. The tour includes an audio commentary.",
"videos": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"
  }
],
"price": "$100.00",
"location": {

```

```
"latitude": "1.287",  
"longitude": "103.805"  
},  
"startingPoint": "Hotel Pickup",  
"endingPoint": "Hotel Pickup",  
"tourOperatingHours": "9am - 1pm",  
"nearestMRTStation": "Bayfront MRT Station",  
"wheelChairFriendly": "Y",  
"childFriendly": "Y",  
"minimumAge": "12",  
"companyName": "Tour East Singapore",  
"majorStops": "Star Vista",  
"startDate": "2018-10-08T06:55:17.830Z",  
"endDate": "2018-10-08T06:55:17.830Z",  
"supportedLanguage": "en"  
}
```

## Tour Data Schema:

Parameter Name	Parameter Type	Parameter Description																		
uuid	string	Attribute used to uniquely identify an record. Example: 00290ed83551389471abe25eecf4ddb9563																		
name	string	Name of the record. Example: Outdoor Gardens Cruiser Tour																		
type	string	Type in which the record belongs to. Example: Food & Beverages History & Culture Arts Adventure & Sports Nature & Wildlife In-House Multi-Day Packages Others																		
tags	array	Tags pertaining to the record, each item is a string. Example: [Marina Bay]																		
description	string	Field to describe the record Example: Visitors go on an audio-guided tour while travelling on a tram around the green oasis of Gardens by the Bay.																		
body	string	Content body of the record Example: The breathtaking and eco-friendly Gardens by the Bay is an ideal destination to spend a few quiet moments in the middle of Singapore's bustling city centre. Visitors ...																		
location	object	Location of the record, containing the following properties: <table border="1"> <tr> <td>latitude</td><td>string</td><td>Example: 1.287</td></tr> <tr> <td>longitude</td><td>String</td><td>Example: 103.805</td></tr> </table>	latitude	string	Example: 1.287	longitude	String	Example: 103.805												
latitude	string	Example: 1.287																		
longitude	String	Example: 103.805																		
address	object	Structured address of the record, containing the following properties: <table border="1"> <tr> <td>block</td><td>string</td><td>Example: 323</td></tr> <tr> <td>streetName</td><td>string</td><td>Example: Alexandra Road</td></tr> <tr> <td>floorNumber</td><td>string</td><td>Example: 1</td></tr> <tr> <td>unitNumber</td><td>string</td><td>Example: 1232</td></tr> <tr> <td>buildingName</td><td>string</td><td>Example: Alexandra Point</td></tr> <tr> <td>postalCode</td><td>string</td><td>Example: 159972</td></tr> </table>	block	string	Example: 323	streetName	string	Example: Alexandra Road	floorNumber	string	Example: 1	unitNumber	string	Example: 1232	buildingName	string	Example: Alexandra Point	postalCode	string	Example: 159972
block	string	Example: 323																		
streetName	string	Example: Alexandra Road																		
floorNumber	string	Example: 1																		
unitNumber	string	Example: 1232																		
buildingName	string	Example: Alexandra Point																		
postalCode	string	Example: 159972																		
contact	object	Contact numbers of the record, containing the following properties: <table border="1"> <tr> <td>primaryContactNo</td><td>string</td><td>Example: +65 6828 8888</td></tr> <tr> <td>secondaryContactNo</td><td>string</td><td>Example: +65 6828 8878</td></tr> <tr> <td>otherContactNo</td><td>string</td><td>Example: +65 6828 8868</td></tr> </table>	primaryContactNo	string	Example: +65 6828 8888	secondaryContactNo	string	Example: +65 6828 8878	otherContactNo	string	Example: +65 6828 8868									
primaryContactNo	string	Example: +65 6828 8888																		
secondaryContactNo	string	Example: +65 6828 8878																		
otherContactNo	string	Example: +65 6828 8868																		

thumbnails	array	<p>Image thumbnails to represent the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>						
images	array	<p>Images related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>						
documents	array	<p>Documents related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>						
videos	array	<p>Videos related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>						
companyName	string	Tour company name. Example: Tour East Singapore						
officialWebsite	string	The official website of the record. Example: <a href="http://www.gardensbythebay.com.sg/en/plan-your-visit/tours-and-trails/outdoor-garden-cruiser-tours.html">http://www.gardensbythebay.com.sg/en/plan-your-visit/tours-and-trails/outdoor-garden-cruiser-tours.html</a>						

officialEmail	String	The official email of the record. Example: feedback@gardensbythebay.com.sg
nearestMrtStation	string	The nearest MRT Station to the record. Example: Bayfront MRT Station
singaporeTourismAwards	string	Field to declare if the record has been given an award. Example: Y N
tourPrice	string	Tour price. Example: \$100.00
startingPoint	string	Tour starting point. Example: Hotel Pickup
endingPoint	string	Tour ending point. Example: Bayfront MRT Station
majorStops	string	Tour major stops. Example: Flower Dome, Cloud Forest
frequencyOfTours	string	Tour frequency. Example: Every Monday, Wednesday, Friday
tourDuration	string	Tour duration. Example: 4 hours
tourOperatingHours	string	Tour operating hours. Example: 9am – 1pm
startDate	date-time	Tour start date. Example: 2017-10-30T20:20:00Z
endDate	date-time	Tour end date. Example: 2017-12-30T20:20:00Z
language	string	Language in which the tour is conducted. Example: English
wheelChairFriendly	string	Whether the record is wheelchair-friendly. Example: Y N
childFriendly	string	Whether the record is child-friendly. Example: Y N
minimumAge	string	Minimum age limit of the tour. Example: 12
supportedLanguage	string	Supported language for this POI Example: en   zh-cn   zh-tw   ja   ko



## 2.10. Venues

The APIs listed below allow contribution of Venues POIs and its details (e.g. type, amenities, business hours) . Venue POI can be retrieved by uuid or keyword search thereafter.

POST <b>createVenue</b> <a href="https://tih-api.stb.gov.sg/content/v1/admin/venue">https://tih-api.stb.gov.sg/content/v1/admin/venue</a>		
Allows the creation of a Venue POI. To create successfully, the following input parameters are mandatory: name, type, tags, description and body.		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Venue to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "uuid": "",   "officialEmail": "enquiry@changicove.com",   "contact": {     "primaryContactNo": "+6569226122",     "secondaryContactNo": "",     "otherContactNo": ""   },   "nearestMrtStation": "Pasir Ris",   "officialWebsite": "http://www.changicove.com/",   "body": "&lt;p&gt;Set on 4 hectares of land by the Johor Strait, this hotel and conference centre, with a sleek and modern facade, is a 5-minute walk from a bus stop, and 2 km from Changi Beach Park. \r\n\r\nMinimalist rooms with hanging bean bag lounge chairs and hardwood floors, feature free Wi-Fi, flat-screen TVs, Nespresso machines and designer toiletries.\r\n\r\nParking is free and so is a breakfast buffet, which is served in a chic lobby restaurant/bar. Other amenities include conference facilities and laundry service.&lt;br&gt;&lt;/p&gt;",   "thumbnails": [{     "url": "",     "uuid": "10196187c29870f441da1580a2e0268763d",   }],   "videos": [],   "images": [{     "url": "",     "uuid": "101e81ea7d85aff46bd813ec0a8d1e5a24a",   }],   "amenities": "Carpark,Children's Club,Free Wi-Fi,Laundry &amp; Dry Cleaning", }</pre>		

```

    "capacity": "200",
    "pricing": "168",
    "numberOfHalls": "10",
    "configurable": "",
    "exhibitionSpace": "",
    "ceilingHeight": "",
    "numberOfMeetingRooms": "25",
    "categoryDescription": "Venues",
    "tags": [
      "Event Organisers",
      "Architecture",
      "Short Stay"
    ],
    "description": "Spaces at Changi Cove are uniquely designed, creative and intimate - catered for all types of events and parties.",
    "address": {
      "postalCode": "509866",
      "block": "",
      "streetName": "351 Cranwell Rd",
      "floorNumber": "",
      "unitNumber": "",
      "buildingName": "Changi Cove Hotel"
    },
    "name": "Changi Cove",
    "location": {
      "latitude": 1.388916,
      "longitude": 103.976492
    },
    "type": "MICE",
    "supportedLanguage": "en"
  }

```

DELETE

deleteVenue

https://tih-api.stb.gov.sg/content/v1/admin/venue/{uuid}

Allows the deletion of an existing Venue POI through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchVenuesByKeyword API.

REQUEST		
Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify a Venue	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

{

---

```
"uuid": "0082f3218119c584b9d922cfd2ed2170ffa",  
"language": "EN",  
}
```

PUT

updateVenue  
https://tih-api.stb.gov.sg/content/v1/admin/Venue/{uuid}

Allows an existing Venue POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchVenuesByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify a Venue. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Venue to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

body Example

```
{  "uuid": "1019618abc9870f441da1580a2e0268763d",  "officialEmail": "enquiry@changicove.com",  "contact": {    "primaryContactNo": "+6569226122",    "secondaryContactNo": "",    "otherContactNo": ""  },  "nearestMrtStation": "Pasir Ris",  "officialWebsite": "http://www.changicove.com/",  "body": "<p>Set on 4 hectares of land by the Johor Strait, this hotel and conference centre, with a sleek and modern facade, is a 5-minute walk from a bus stop, and 2 km from Changi Beach Park. \r\n\r\nMinimalist rooms with hanging bean bag lounge chairs and hardwood floors, feature free Wi-Fi, flat-screen TVs, Nespresso machines and designer toiletries.\r\n\r\nParking is free and so is a breakfast buffet, which is served in a chic lobby restaurant/bar. Other amenities include conference facilities and laundry service.<br></p>",  "thumbnails": [{    "url": "",    "uuid": "10196187c29870f441da1580a2e0268763d",  }],  "videos": [],  "images": [{    "url": "",    "uuid": "101e81ea7d85aff46bd813ec0a8d1e5a24a",  }],  "amenities": "Carpark,Children's Club,Free Wi-Fi,Laundry & Dry Cleaning",  "capacity": "200",  "pricing": "168",  "numberOfHalls": "10",  "configurable": ""}
```

```
"exhibitionSpace": "",
"ceilingHeight": "",
"numberOfMeetingRooms": "25",
"categoryDescription": "Venues",
"tags": [
  "Event Organisers",
  "Architecture",
  "Short Stay"
],
"description": "Spaces at Changi Cove are uniquely designed, creative
and intimate - catered for all types of events and parties.",
"address": {
  "postalCode": "509866",
  "block": "",
  "streetName": "351 Cranwell Rd",
  "floorNumber": "",
  "unitNumber": "",
  "buildingName": "Changi Cove Hotel"
},
"name": "Changi Cove",
"location": {
  "latitude": 1.388916,
  "longitude": 103.976492
},
"type": "MICE",
"supportedLanguage": "en"
}
```

## Venue Data Schema:

Parameter Name	Parameter Type	Parameter Description																		
uuid	string	Attribute used to uniquely identify an record. Example: 00290ed83551389471abe25eecf4ddb9563																		
name	string	Name of the record. Example: Changi Cove																		
type	string	Type in which the record belongs to. Example: Arts & Entertainment   MICE   Sports   Others																		
tags	array	Tags pertaining to the record, each item is a string. Example: [Changi]																		
description	string	Field to describe the record Example: Spaces at Changi Cove are uniquely designed, creative and intimate – catered for all types of events and parties.																		
body	string	Content body of the record Example: Set on 4 hectares of land by the Johor Strait, this hotel and conference centre, with a sleek and modern facade, is a 5-minute walk from a bus stop, and 2 km from Changi Beach Park ...																		
location	object	Location of the record, containing the following properties: <table border="1"> <tr> <td>latitude</td><td>string</td><td>Example: 1.287</td></tr> <tr> <td>longitude</td><td>String</td><td>Example: 103.805</td></tr> </table>	latitude	string	Example: 1.287	longitude	String	Example: 103.805												
latitude	string	Example: 1.287																		
longitude	String	Example: 103.805																		
address	object	Structured address of the record, containing the following properties: <table border="1"> <tr> <td>block</td><td>string</td><td>Example: 323</td></tr> <tr> <td>streetName</td><td>string</td><td>Example: Alexandra Road</td></tr> <tr> <td>floorNumber</td><td>string</td><td>Example: 1</td></tr> <tr> <td>unitNumber</td><td>string</td><td>Example: 1232</td></tr> <tr> <td>buildingName</td><td>string</td><td>Example: Alexandra Point</td></tr> <tr> <td>postalCode</td><td>string</td><td>Example: 159972</td></tr> </table>	block	string	Example: 323	streetName	string	Example: Alexandra Road	floorNumber	string	Example: 1	unitNumber	string	Example: 1232	buildingName	string	Example: Alexandra Point	postalCode	string	Example: 159972
block	string	Example: 323																		
streetName	string	Example: Alexandra Road																		
floorNumber	string	Example: 1																		
unitNumber	string	Example: 1232																		
buildingName	string	Example: Alexandra Point																		
postalCode	string	Example: 159972																		
contact	object	Contact numbers of the record, containing the following properties: <table border="1"> <tr> <td>primaryContactNo</td><td>string</td><td>Example: +65 6828 8888</td></tr> <tr> <td>secondaryContactNo</td><td>string</td><td>Example: +65 6828 8878</td></tr> <tr> <td>otherContactNo</td><td>string</td><td>Example: +65 6828 8868</td></tr> </table>	primaryContactNo	string	Example: +65 6828 8888	secondaryContactNo	string	Example: +65 6828 8878	otherContactNo	string	Example: +65 6828 8868									
primaryContactNo	string	Example: +65 6828 8888																		
secondaryContactNo	string	Example: +65 6828 8878																		
otherContactNo	string	Example: +65 6828 8868																		

thumbnails	array	<p>Image thumbnails to represent the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
images	array	<p>Images related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
documents	array	<p>Documents related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
videos	array	<p>Videos related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
officialWebsite	string	The official website of the record. Example: http://www.bras-basah-complex.com.sg/bbc/						
officialEmail	String	The official email of the record. Example: info@bras-basah-complex.com.sg						

nearestMrtStation	string	The nearest MRT Station to the record. Example: Pasir Ris MRT Station
singaporeTourismAwards	string	Field to declare if the record has been given an award. Example: Y N
pricing	string	Price Example: \$100
numberOfHalls	string	Number of Halls Example: 10
numberOfMeetingRooms	string	Number of Meeting Rooms Example: 25
configurable	string	Configurable Example: Y N
capacity	string	Maximum capacity Example: 1000
exhibitionSpace	string	Exhibition space (in sqm) Example: 20000
ceilingHeight	string	Ceiling height (in m) Example: 10
amenities	string	Useful facilities found in the record. Example: Children's Club, Free Wi-Fi
supportedLanguage	string	Supported language for this POI Example: en   zh-cn   zh-tw   ja   ko



## 2.11. Walking Trails

The APIs listed below allow contribution of Walking Trails POIs and its details (e.g. type, location). Walking Trail POIs can be retrieved by uuid or keyword search thereafter.

<div> <div>POST</div> <div> <b>createWalkingTrail</b>  <a href="https://tih-api.stb.gov.sg/content/v1/admin/walking-trail">https://tih-api.stb.gov.sg/content/v1/admin/walking-trail</a> </div> </div>		
Allows the creation of a Walking Trail POI. To create successfully, the following input parameters are mandatory: name, type, tags, description and body.		
REQUEST		
Parameters	Description	Mandatory
body	JSON which holds all the properties of the Walking Trail to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{   "uuid": "",   "name": "Singapore River Walk",   "type": "History &amp; Culture",   "tags": ["Outdoors"],   "description": "Since 1819, when modern Singapore was founded, the Singapore River has served as an artery of international commerce that drew people from all over the region to work, trade and seek their fortunes on this island. Today, after a major clean-up that ended in 1983, the river continues to bustle with life, flowing past modern skyscrapers and historic buildings.",   "thumbnails": [     {       "uuid": "",       "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"     }   ],   "images": [     {       "uuid": "",       "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"     }   ],   "documents": [     {</pre>		

```
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
"contact": {
  "primaryContactNo": "+65 6828 8888",
  "secondaryContactNo": "",
  "otherContactNo": ""
},
"officialWebsite": "https://roots.sg/visit/trails/singapore-river-walk",
"officialEmail": "info@sgriverwalk.com",
"body": "Since 1819, when modern Singapore was founded, the Singapore River
has served as an artery of international commerce that drew people from all
over the region to work, trade and seek their fortunes on this island. Today,
after a major clean-up that ended in 1983, the river continues to bustle with
life, flowing past modern skyscrapers and historic buildings.",
"videos": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
]
}
```

**POST**

## createWalkingTrailDetails

<https://tih-api.stb.gov.sg/content/v1/admin/walking-trail/{uuid}/detail>

Allows the creation of a Walking Trail itinerary. To create successfully, the following input parameters are mandatory: name, type, tags, description and body. A Walking Trail record need to be created before creating 1/multiple Walking Trail Details itinerary record(s). The uuid is the identifier for the main Walking Trail record.

### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify a Walking Trail record. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Walking Trail Details to be created. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

### Example

```
{
  "uuid": "0095e37c4d700ac4220acac5f82bd74077a",
  "name": "National Gallery Singapore - Jubilee Walk",
  "type": "History & Culture",
  "tags": ["Outdoors"],
  "description": "The National Gallery Singapore occupies two historic buildings: the former City Hall and Supreme Court. City Hall, which was completed in 1929, was where Japanese forces officially surrendered to the Allied Forces in 1945. The Supreme Court, which opened in 1939, was where war crime trials were held in 1946.",
  "officialWebsite": "https://roots.sg/visit/trails/jubilee-walk",
  "supportedLanguage": [
    "EN"
  ],
  "formattedAddress": "Formatted Address",
  "location": {
    "latitude": "1.287",
    "longitude": "103.805"
  },
  "contact": {
    "primaryContactNo": "+65 6828 8888",
    "secondaryContactNo": "",
    "otherContactNo": ""
  },
  "thumbnails": [
    {
      "uuid": "",

```

```
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
"images": [
  {
    "uuid": "",
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
"documents": [
  {
    "uuid": "",
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
],
"videos": [
  {
    "uuid": "",
    "url":
    "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
]
}
```

## DELETE

### deleteWalkingTrail

<https://tih-api.stb.gov.sg/content/v1/admin/walking-trail/{uuid}>

Allows the deletion of an existing Walking Trail POI through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchWalkingTrailByKeyword API.

It is recommended that the related WalkingTrailDetails record(s) is to be deleted.

#### REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify a Walking Trail	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

#### Example

```
{
  "uuid": "0095e37c4d700ac4220acac5f82bd74077a",
  "language": "EN",
}
```

## DELETE

### deleteWalkingTrailDetail

<https://tih-api.stb.gov.sg/content/v1/admin/walking-trail/{uuid}/detail/{uid}>

Allows the deletion of an existing Walking Trail itinerary detail through the use of a unique identifier. The acronym for the unique identifier is uid. This uid is created when you create Walking Trail Detail. If you have not documented the uid, you can fetch it by using getWalkingTrailDetailsByUuid API.

#### REQUEST

Parameters	Description	Mandatory
uid	Attribute used to uniquely identify a Walking Trail details	Yes
uuid	Attribute used to uniquely identify a Walking Trail parent	
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

#### Example

```
{
  "uuid": "1095e37c4d7abcd4220acac5f82bd74077a",
  "parentuuid": "0095e37c4d700ac4220acac5f82bd74077a",
  "language": "EN",
}
```

PUT

updateWalkingTrail  
https://tih-api.stb.gov.sg/content/v1/admin/walking-trail/{uuid}

Allows an existing Walking Trail POI to be updated through the use of a unique identifier. The acronym for the unique identifier is uuid. This uuid is created when you submit a content. If you have not documented the uuid, you can fetch it by using searchWalkingTrailByKeyword API.

REQUEST

Parameters	Description	Mandatory
uuid	Attribute used to uniquely identify a Walking Trail. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of a Walking Trail to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No

Example

```
{  "uuid": "0095e37c4d700ac4220acac5f82bd74077a",  "name": "Singapore River Walk",  "type": "History & Culture",  "tags": ["Outdoors"],  "description": "Since 1819, when modern Singapore was founded, the Singapore River has served as an artery of international commerce that drew people from all over the region to work, trade and seek their fortunes on this island. Today, after a major clean-up that ended in 1983, the river continues to bustle with life, flowing past modern skyscrapers and historic buildings.",  "thumbnails": [    {      "uuid": "",      "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"    }  ],  "images": [    {      "uuid": "",      "url": "http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c52"    }  ],  "documents": [    {      "uuid": "",
```

```
"url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
}
],
"contact": {
  "primaryContactNo": "+65 6828 8888",
  "secondaryContactNo": "",
  "otherContactNo": ""
},
"officialWebsite": "https://roots.sg/visit/trails/singapore-river-walk",
"officialEmail": "info@sgriverwalk.com",
"body": "Since 1819, when modern Singapore was founded, the Singapore River
has served as an artery of international commerce that drew people from all
over the region to work, trade and seek their fortunes on this island. Today,
after a major clean-up that ended in 1983, the river continues to bustle with
life, flowing past modern skyscrapers and historic buildings.",
"videos": [
  {
    "uuid": "",
    "url":
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c
52"
  }
]
}
```

PUT	<b>updateWalkingTrailDetails</b> <a href="https://tih-api.stb.gov.sg/content/v1/admin/walking-trail/{uuid}/detail/{uuid}">https://tih-api.stb.gov.sg/content/v1/admin/walking-trail/{uuid}/detail/{uuid}</a>	
Allows an existing Walking Trail itinerary Details to be updated through the use of a unique identifier. The acronym for the unique identifier is uid. This uid is created when you create Walking Trail Details. If you have not documented the uid, you can fetch it by using getWalkingTrailDetailsByUuid API.		
REQUEST		
Parameters	Description	Mandatory
uid	Attribute used to uniquely identify a Walking Trail Detail. Refer to <i>Example</i> .	Yes
uuid	Attribute used to uniquely identify a Walking Trail parent. Refer to <i>Example</i> .	Yes
body	JSON which holds all the properties of the Walking Trail Details to be updated. Refer to <i>Example</i> .	Yes
language	Language type [EN   ZH-CN   ZH-TW   JA   KO] If no language is supplied, EN will be the default language applied.	No
Example		
<pre>{  "uuid": "1095e37c4d7abcd4220acac5f82bd74077a",  "parentuuid": "0095e37c4d700ac4220acac5f82bd74077a",  "name": "National Gallery Singapore - Jubilee Walk",  "type": "History &amp; Culture",  "tags": ["Outdoors"],  "description": "The National Gallery Singapore occupies two historic buildings: the former City Hall and Supreme Court. City Hall, which was completed in 1929, was where Japanese forces officially surrendered to the Allied Forces in 1945. The Supreme Court, which opened in 1939, was where war crime trials were held in 1946.",  "officialWebsite": "https://roots.sg/visit/trails/jubilee-walk",  "supportedLanguage": [    "EN"  ],  "formattedAddress": "Formatted Address",  "location": {    "latitude": "1.287",    "longitude": "103.805"  },  "contact": {    "primaryContactNo": "+65 6828 8888",    "secondaryContactNo": "",    "otherContactNo": ""  },  }</pre>		



```
"thumbnails": [  
  {  
    "uuid": "",  
    "url":  
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c  
52"  
  }  
],  
"images": [  
  {  
    "uuid": "",  
    "url":  
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c  
52"  
  }  
],  
"documents": [  
  {  
    "uuid": "",  
    "url":  
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c  
52"  
  }  
],  
"videos": [  
  {  
    "uuid": "",  
    "url":  
"http://api.tih.local/media/v1/download/uuid/10168fc9bf8091f4a4186baeec2f71c3c  
52"  
  }  
]  
}
```

## Walking Trail Data Schema:

Parameter Name	Parameter Type	Parameter Description									
uuid	string	Attribute used to uniquely identify an record. Example: 00290ed83551389471abe25eecf4ddb9563									
name	string	Name of the record. Example: Singapore River Walk									
type	string	Type in which the record belongs to. Example: Arts History & Culture Food & Beverages Event & Festivities See & Do Shops Others									
tags	array	Tags pertaining to the record, each item is a string. Example: [Outdoors]									
description	string	Field to describe the record Example: Since 1819, when modern Singapore was founded, the Singapore River has served as an artery of international commerce that drew people from all over the region.									
body	string	Content body of the record Example: Since 1819, when modern Singapore was founded, the Singapore River has served as an artery of international commerce that drew people from all over the region to work, trade and seek their fortunes on this island. Today, ...									
contact	object	Contact numbers of the record, containing the following properties: <table border="1"> <tr> <td>primaryContactNo</td><td>string</td><td>Example: +65 6828 8888</td></tr> <tr> <td>secondaryContactNo</td><td>string</td><td>Example: +65 6828 8878</td></tr> <tr> <td>otherContactNo</td><td>string</td><td>Example: +65 6828 8868</td></tr> </table>	primaryContactNo	string	Example: +65 6828 8888	secondaryContactNo	string	Example: +65 6828 8878	otherContactNo	string	Example: +65 6828 8868
primaryContactNo	string	Example: +65 6828 8888									
secondaryContactNo	string	Example: +65 6828 8878									
otherContactNo	string	Example: +65 6828 8868									
thumbnails	array	Image thumbnails to represent the record, each item is an object that may contain either of the following properties: <table border="1"> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a></td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>			
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563									
url	string	To use external media Example: <a href="http://bit.do/ePqpB">http://bit.do/ePqpB</a>									

images	array	<p>Images related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
documents	array	<p>Documents related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
videos	array	<p>Videos related to the record, each item is an object that may contain either of the following properties:</p> <table> <tr> <td>uuid</td><td>string</td><td>To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563</td></tr> <tr> <td>url</td><td>string</td><td>To use external media Example: http://bit.do/ePqpB</td></tr> </table>	uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563	url	string	To use external media Example: http://bit.do/ePqpB
uuid	string	To use TIH media Example: 00290ed83551389471abe25eecf4ddb9563						
url	string	To use external media Example: http://bit.do/ePqpB						
officialWebsite	string	The official website of the record. Example: https://roots.sg/visit/trails/singapore-river-walk						
officialEmail	String	The official email of the record. Example: info@sgriverwalk.com						
supportedLanguage	string	Supported language for this POI Example: en   zh-cn   zh-tw   ja   ko						

### 3. Content User API

#### 3.1. General

This section provides generic APIs for developers to use and gives a broad overview of the content found in the Content API.

GET	autoCompleteByType		
	<a href="https://tih-api.stb.gov.sg/content/v1/autocomplete/type">https://tih-api.stb.gov.sg/content/v1/autocomplete/type</a>		
Provides a list of autocomplete results.			
REQUEST			
Parameters	Description	Mandatory	Example
type	name   description   tag	No	name
input	Input to do an auto complete search on.	Yes	Bay

GET

getTags

https://tih-api.stb.gov.sg/content/v1/tag

Retrieves the full list of tags available.

REQUEST

Parameters	Description	Mandatory	Example
nextToken	Parameter which can be used to obtain the subsequent set of records.	No	
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

GET		<b>listDatasets</b> <a href="https://tih-api.stb.gov.sg/content/v1/datasets">https://tih-api.stb.gov.sg/content/v1/datasets</a>	
Retrieves the full list of datasets available.			
REQUEST			
Parameters	Description	Mandatory	Example
Nil			
RESPONSE			
Accommodation; Attractions; Bars_Clubs; Event; Food_Beverages; Shops; Tour; Venue; Walking_Trail; Precincts			

GET	<b>searchCompanyByKeyword</b> <a href="https://tih-api.stb.gov.sg/content/v1/company">https://tih-api.stb.gov.sg/content/v1/company</a>		
Performs a search for companies based on the keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
keyword	Keyword which will be used to search for.	Yes	Singapore Tourism Board
nextToken	Next Token which will be used to retrieve the next set of records.	No	

<div> <div>GET</div> <div> <b>searchKeywordByMultiDataset</b>  <a href="https://tih-api.stb.gov.sg/content/v1/search/all">https://tih-api.stb.gov.sg/content/v1/search/all</a> </div> </div>			
Provides the ability to search through multiple datasets for a specific keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
dataset	General search term Note: Use General Dataset API to get all the Dataset values [accommodation; attractions; bars_clubs; event; food_beverages; shops; tour; venue; walking_trail; precincts].	Yes	accommodation
keyword	Keyword to look for when performing the search function.	No	Hotels
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board
sortBy	Field name to sort [name   createDate   updatedAt].	No	name
sortOrder	Sort order [asc   desc].	No	asc
nextToken	Next Token which will be used to retrieve the next set of records.	No	
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

### 3.2. Accommodation

The APIs listed below allow extraction of Accommodation POIs and its details (e.g. type, amenities, room rates). Accommodation POIs can be retrieved by uuid or keyword search.

<div>GET</div> <div>getAccommodationByUuids</div> <div><a href="https://tih-api.stb.gov.sg/content/v1/accommodation">https://tih-api.stb.gov.sg/content/v1/accommodation</a></div>			
Retrieves the full details of multiple Accommodations POIs by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new accommodation using createAccommodation from content provider API. You can retrieve uuids from Accommodation API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify an Accommodation. This API allows the retrieval of multiple uuids	Yes	001f0b4d5dadde543f080fdb89cee195a93, 00157c3bd7eed474d8a865f7825943d1051
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

GET <b>listAccommodationTypes</b> <a href="https://tih-api.stb.gov.sg/content/v1/accommodation/types">https://tih-api.stb.gov.sg/content/v1/accommodation/types</a>			
Retrieve a list of Accommodation types such as backpackers hostels, hotels, resorts, service apartments, and others.			
REQUEST			
Parameters	Description	Mandatory	Example
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en
RESPONSE			
Backpacker Hostels; Hotels; Resorts; Serviced Apartments; Others			

GET <b>searchAccommodationByKeyword</b> <a href="https://tih-api.stb.gov.sg/content/v1/accommodation/search">https://tih-api.stb.gov.sg/content/v1/accommodation/search</a>			
Performs a search on all Accommodations POIs based on keyword as the search parameter. The keyword will match with names, descriptions and tags, returning you the most relevant Accommodation.			
REQUEST			
Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Hotels
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board
nextToken	Next Token which will be used to retrieve the next set of records	No	
sortBy	Field name to sort [name   type   description   origin   source   nearestMrtStation]	No	name
sortOrder	Sort order [ asc   desc ]	No	asc



---

language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en
----------	--	----	----

### 3.3. Attractions

The APIs listed below allow extraction of Attractions POIs and its details (e.g. type, amenities, business hours). Attraction POIs can be retrieved by uuid or keyword search.

GET <b>getAttractionsByUuids</b> <a href="https://tih-api.stb.gov.sg/content/v1/attractions">https://tih-api.stb.gov.sg/content/v1/attractions</a>			
Retrieves the full details of the Attraction by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new Attraction using createAttraction from content provider API. You can retrieve uuids from Attraction API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify an Attraction. This API allows the retrieval of multiple uuids	Yes	00223f657552434463 cb0c1ddc603acd98b, 0020b12e16e6eba4d5 7b5c5176bada84b6d
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

GET <b>listAttractionsTypes</b> <a href="https://tih-api.stb.gov.sg/content/v1/attractions/types">https://tih-api.stb.gov.sg/content/v1/attractions/types</a>			
Retrieve a list of Attraction types, for example, Adventure.			
REQUEST			
Parameters	Description	Mandatory	Example
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en
RESPONSE			
Adventure; Arts; History & Culture; Leisure & Recreation; Nature & Wildlife; Others			

<div> <div>GET</div> <div> <b>searchAttractionsByKeyword</b>  <a href="https://tih-api.stb.gov.sg/content/v1/attractions/search">https://tih-api.stb.gov.sg/content/v1/attractions/search</a> </div> </div>			
Performs a search on all Attractions based on keyword as the search parameter. The keyword will match with names, description and tags, returning you the most relevant Attractions.			
REQUEST			
Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Museum
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board or HungryGoWhere
nextToken	Next Token which will be used to retrieve the next set of records	No	
sortBy	Field name to sort [name   type   description   origin   source   nearestMrtStation]	No	name
sortOrder	Sort order [asc   desc]	No	asc
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

### 3.4. Bars and Clubs

The APIs listed below allow extraction of Bars and Clubs POIs and its details (e.g. type, amenities, business hours). Bars and Clubs POIs can be retrieved by uuid or keyword search.

GET <b>getBarsClubsByUuids</b> <a href="https://tih-api.stb.gov.sg/content/v1/bars-clubs">https://tih-api.stb.gov.sg/content/v1/bars-clubs</a>			
Retrieves the full details of multiple Bars and Clubs POIs by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new Bars & Clubs using createBarsClubs from content provider API. You can retrieve uuids from Bars & Clubs API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify Bars or Clubs. This API allows the retrieval of multiple uuids	Yes	00223f657552434463 cb0c1ddc603acd98b; 0020b12e16e6eba4d5 7b5c5176bada84b6d
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

GET <b>listBarsClubsTypes</b> <a href="https://tih-api.stb.gov.sg/content/v1/bars-clubs/types">https://tih-api.stb.gov.sg/content/v1/bars-clubs/types</a>			
Retrieve a list of Bars and Clubs types, for example bars.			
REQUEST			
Parameters	Description	Mandatory	Example
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en
RESPONSE			
Bars; Clubs; Others			

**GET**

## searchBarsClubsByKeyword

<https://tih-api.stb.gov.sg/content/v1/bars-clubs/search>

Performs a search on all Bars and Clubs POIs based on keyword as the search parameter. The keyword will match with names, description and tags, returning you the most relevant Bars and Clubs.

### REQUEST

Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Night Life
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board or HungryGoWhere
nextToken	Next Token which will be used to retrieve the next set of records	No	
sortBy	Field name to sort [name   type   description   origin   source   nearestMrtStation]	No	name
sortOrder	Sort order [asc   desc]	No	asc
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

### 3.5. Cruises

The APIs listed below allow extraction of Cruise and its details (e.g. sailing dates, cruise services). Cruise POIs can be retrieved by uuid or keyword search.

<div> <div>GET</div> <div> <b>getCruisesByUuids</b>  <a href="https://tih-api.stb.gov.sg/content/v1/cruises">https://tih-api.stb.gov.sg/content/v1/cruises</a> </div> </div>			
Retrieves the full details of multiple Cruise POIs by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new Cruise using createCruise from Content Provider API. You can retrieve uuids from Cruise API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify Cruises. This API allows the retrieval of multiple uuids	Yes	00223f657552434463 cb0c1ddc603acd98b, 0020b12e16e6eba4d5 7b5c5176bada84b6d
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

<div> <div>GET</div> <div> <b>searchCruisesByKeyword</b>  <a href="https://tih-api.stb.gov.sg/content/v1/cruises/search">https://tih-api.stb.gov.sg/content/v1/cruises/search</a> </div> </div>			
<p>Performs a search on all Cruises POIs based on keyword as the search parameter. The keyword will match with names, description and tags, returning you the most relevant Cruises.</p>			
REQUEST			
Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Marina Bay
startMonth	Sailing start month	No	08/2019
endMonth	Sailing end month	No	08/2019
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board
page	Page number for the pagination of the returned records, starting from 1 for 1st page. Default value: 1	No	1
pageSize	Page size for the pagination of the returned records. Minimum value: 1 Maximum value: 20 Default value: 20	No	10
sortBy	Field name to sort [name   source] Default: when no "sortBy" field is specified, return the most recent/matching records first. "sortOrder" parameter is ignored when "sortBy" is not specified.	No	name
sortOrder	Sort order [asc   desc] Default value: asc (when sortBy field is specified)	No	asc
language	Language type [en   zh-cn   zh-tw   ja   ko]	No	en

	If no language is supplied, en will be the default language applied.		
--	--	--	--

GET <b>listCruisesTypes</b> <a href="https://tih-api.stb.gov.sg/content/v1/cruises/types">https://tih-api.stb.gov.sg/content/v1/cruises/types</a>			
Retrieve a list of Cruises types, for example Contemporary, Premium, or Luxury.			
REQUEST			
Parameters	Description	Mandatory	Example
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en
RESPONSE			
Contemporary; Premium; Luxury			



### 3.6. Events

The APIs listed below allow extraction of Events POIs and its details (e.g. type, location, price). Event POI can be retrieved by uuid or keyword search.

GET <b>getEventByUuids</b> <a href="https://tih-api.stb.gov.sg/content/v1/event">https://tih-api.stb.gov.sg/content/v1/event</a>			
Retrieves the full details of multiple Events POIs by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new Events using createEvent from content provider API. You can retrieve uuids from Events API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify Events. This API allows the retrieval of multiple uuids	Yes	00223f657552434463 cb0c1ddc603acd98b, 0020b12e16e6eba4d5 7b5c5176bada84b6d
language	Language type [en]	No	en

GET <b>getEventDetailsByUuid</b> <a href="https://tih-api.stb.gov.sg/content/v1/event/uuid/{uuid}/detail">https://tih-api.stb.gov.sg/content/v1/event/uuid/{uuid}/detail</a>			
Retrieves the detail of a sub-Event hosted by Main Event POI, by providing Main Event unique identifier. The acronym for the unique identifier is uuid. The uuid is generated while creating new Events using createEvent from content provider API. You can retrieve uuids from Events API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify an Event	Yes	0026b01ab0db6ab4f5 d9d119ab0cf04e401
language	Language type [en]	No	en

GET <b>listEventTypes</b> <a href="https://tih-api.stb.gov.sg/content/v1/event/types">https://tih-api.stb.gov.sg/content/v1/event/types</a>			
Retrieve a list of Event types.			
REQUEST			
Parameters	Description	Mandatory	Example
language	Language type [en]	No	en
RESPONSE			
Arts; Attractions; Entertainment; Food & Beverages; History & Culture; MICE; Nature & Wildlife; Shopping; Sports; Others			

GET <b>searchEventByKeyword</b> <a href="https://tih-api.stb.gov.sg/content/v1/event/search">https://tih-api.stb.gov.sg/content/v1/event/search</a>			
Performs a search on all Events POIs based on keyword as the search parameter. The keyword will match with names, description and tags, returning you the most relevant Events.			
REQUEST			
Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Parade
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board or HungryGoWhere
sortBy	Field name to sort [name   type   description   origin   nearestMrtStation]	No	name
sortOrder	Sort order [asc   desc]	No	asc
nextToken	Next Token which will be used to retrieve the next set of records	No	
language	Language type [en]	No	en

### 3.7. Food & Beverages

The APIs listed below allow extraction of Food and Beverages POIs and its details (e.g. type, amenities, business hours). Food and Beverages POIs can be retrieved by uuid or keyword search.

<div> <div>GET</div> <div> <b>getFoodBeveragesByUuids</b>  <a href="https://tih-api.stb.gov.sg/content/v1/food-beverages">https://tih-api.stb.gov.sg/content/v1/food-beverages</a> </div> </div>			
Retrieves the full details of multiple Food and Beverage establishments by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new Food & Beverages using createFoodBeverages from content provider API. You can retrieve uuids from Food and Beverages API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify Food and Beverages establishments. This API allows the retrieval of multiple uuids	Yes	005e20e4c16d1d044d2b1da0cac19655517; 1015112237114ca4c71a550efdb06b574c2
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

<div> <div>GET</div> <div> <b>listFoodBeveragesTypes</b>  <a href="https://tih-api.stb.gov.sg/content/v1/food-beverages/types">https://tih-api.stb.gov.sg/content/v1/food-beverages/types</a> </div> </div>			
Retrieve a list of Food and Beverage establishment types, for example café.			
REQUEST			
Parameters	Description	Mandatory	Example
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en
RESPONSE			
Café; Hawker Centres ; Restaurants; Others			

**GET**

## searchFoodBeveragesByKeyword

<https://tih-api.stb.gov.sg/content/v1/food-beverages/search>

Performs a search on all Food and Beverage establishments based on keyword as the search parameter. The keyword will match with names, description and tags, returning you the most relevant Food and Beverage establishment.

### REQUEST

Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Restaurant
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board or HungryGoWhere
nextToken	Next Token which will be used to retrieve the next set of records	No	
sortBy	Field name to sort [name   type   description   origin   nearestMrtStation]	No	name
sortOrder	Sort order [asc   desc]	No	asc
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

### 3.8. Malls and Shops

The APIs listed below allow extraction of Malls and Shops POIs and its details (e.g. type, amenities, business hours). Malls and Shops POIs can be retrieved by uuid or keyword search.

GET <b>getShopsByUuids</b> <a href="https://tih-api.stb.gov.sg/content/v1/shops">https://tih-api.stb.gov.sg/content/v1/shops</a>			
Retrieves the full details of multiple Malls and Shops POIs by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new Malls & Shops using createShops from content provider API. You can retrieve uuids from Malls & Shops API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify Malls and Shops. This API allows the retrieval of multiple uuids	Yes	00223f657552434463 cb0c1ddc603acd98b; 0020b12e16e6eba4d5 7b5c5176bada84b6d
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

GET <b>listShopsTypes</b> <a href="https://tih-api.stb.gov.sg/content/v1/shops/types">https://tih-api.stb.gov.sg/content/v1/shops/types</a>			
Retrieve a list of Malls and Shops types, for example bazaar and flea markets.			
REQUEST			
Parameters	Description	Mandatory	Example
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en
RESPONSE			
Bazaars & Flea Markets; Boutiques; Department Stores; Malls; Others			

**GET**

## searchShopsByKeyword

<https://tih-api.stb.gov.sg/content/v1/shops/search>

Performs a search on all Malls and Shops POIs based on keyword as the search parameter. The keyword will match with names, description and tags, returning you the most relevant Malls and Shops.

### REQUEST

Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Orchard
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board or HungryGoWhere
nextToken	Next Token which will be used to retrieve the next set of records	No	
sortBy	Field name to sort [name   type   description   origin   source   nearestMrtStation]	No	name
sortOrder	Sort order [asc   desc]	No	asc
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

### 3.9. Precincts

The APIs listed below allow extraction of Precinct and its details (e.g. perimeter, recommended dwell time). Precinct POIs can be retrieved by uuid or keyword search.

GET <b>getPrecinctsByUuids</b> <a href="https://tih-api.stb.gov.sg/content/v1/precincts">https://tih-api.stb.gov.sg/content/v1/precincts</a>			
Retrieves the full details of multiple Precincts POIs by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new Precinct using createPrecinct from content provider API. You can retrieve uuids from Precinct API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify Precincts. This API allows the retrieval of multiple uuids	Yes	00223f657552434463 cb0c1ddc603acd98b, 0020b12e16e6eba4d5 7b5c5176bada84b6d
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

**GET**

## searchPrecinctsByKeyword

<https://tih-api.stb.gov.sg/content/v1/precincts/search>

Performs a search on all Precincts POIs based on keyword as the search parameter. The keyword will match with names, description and tags, returning you the most relevant Precincts.

### REQUEST

Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Orchard
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board
page	Page number for the pagination of the returned records, starting from 1 for 1st page. Default value: 1	No	1
pageSize	Page size for the pagination of the returned records. Minimum value: 1 Maximum value: 20 Default value: 20	No	10
sortBy	Field name to sort [name   source] Default: when no "sortBy" field is specified, return the most recent/matching records first. "sortOrder" parameter is ignored when "sortBy" is not specified.	No	name
sortOrder	Sort order [asc   desc] Default value: asc (when sortBy field is specified)	No	asc
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en



**GET**

## searchByPrecinctUuid

<https://tih-api.stb.gov.sg/content/v1/search/precinct>

Provides the ability to search through multiple datasets within a specified precinct identified by a unique identifier (uuid).

### REQUEST

Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify a Precinct.	Yes	00223f657552434463 cb0c1ddc603acd98b
dataset	Category of content to be retrieved [accommodation, attractions, bars_clubs, event, food_beverages, shops, tour, venue, walking_trail]. Default: when no value is specified, system will search through all datasets	No	accommodation, attractions
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board
page	Page number for the pagination of the returned records, starting from 1 for 1st page. Default value: 1	No	1
pageSize	Page size for the pagination of the returned records. Minimum value: 1 Maximum value: 20 Default value: 20	No	10
sortBy	Field name to sort [name   category   source] Default: when no "sortBy" field is specified, return the most recent/matching records first. "sortOrder" parameter is ignored when "sortBy" is not specified.	No	name

---

sortOrder	Sort order [asc   desc] Default value: asc (when sortBy field is specified)	No	asc
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

### 3.10. Tours

The APIs listed below allow extraction of Tours POIs and its details (e.g. type, major stops, tour operating hours). Tour POIs can be retrieved by uuid or keyword search.

GET <b>getTourByUuids</b> <a href="https://tih-api.stb.gov.sg/content/v1/tour">https://tih-api.stb.gov.sg/content/v1/tour</a>			
Retrieves the full details of multiple Tours POIs by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new Tours using createTour from content provider API. You can retrieve uuids from Tours API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify a Tour. This API allows the retrieval of multiple uuids	Yes	013bb32ef9bd3fc43fa91d 06a4c67ef9243; 01378b2f4539a004d0faf7 806c938af0e6f
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

GET <b>listTourTypes</b> <a href="https://tih-api.stb.gov.sg/content/v1/tour/types">https://tih-api.stb.gov.sg/content/v1/tour/types</a>			
Retrieve a list of Tour types, for example adventure and sports.			
REQUEST			
Parameters	Description	Mandatory	Example
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en
RESPONSE			
Adventure & Sports; Arts; Food & Beverages; History & Culture; In-House; Multi-Day Packages; Nature & Wildlife; Sightseeing; Others			

<div> <div>GET</div> <div> <b>searchTourByKeyword</b>  <a href="https://tih-api.stb.gov.sg/content/v1/tour/search">https://tih-api.stb.gov.sg/content/v1/tour/search</a> </div> </div>			
Performs a search on all Tours POIs based on keyword as the search parameter. The keyword will match with names, description and tags, returning you the most relevant Tours.			
REQUEST			
Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Raffles
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board or HungryGoWhere
nextToken	Next Token which will be used to retrieve the next set of records	No	
sortBy	Field name to sort [name   type   description   origin   nearestMrtStation]	No	name
sortOrder	Sort order [asc   desc]	No	asc
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

### 3.11. Venues

The APIs listed below allow extraction of Venues POIs and its details (e.g. type, amenities, business hours). Venue POIs can be retrieved by uuid or keyword search.

GET <b>getVenueByUuids</b> <a href="https://tih-api.stb.gov.sg/content/v1/venue">https://tih-api.stb.gov.sg/content/v1/venue</a>			
Retrieves the full details of multiple Venues POIs by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new Venue using createVenue from content provider API. You can retrieve uuids from Venue API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify a Venue. This API allows the retrieval of multiple uuids	Yes	00223f657552434463 cb0c1ddc603acd98b, 0020b12e16e6eba4d5 7b5c5176bada84b6d
language	Language type [en]	No	en

GET <b>listVenueTypes</b> <a href="https://tih-api.stb.gov.sg/content/v1/venue/types">https://tih-api.stb.gov.sg/content/v1/venue/types</a>			
Retrieve a list of Venue types, for example Sports.			
REQUEST			
Parameters	Description	Mandatory	Example
language	Language type [en]	No	en
RESPONSE			
Arts & Entertainment; MICE, Sports; Others			

**GET**

## searchVenueByKeyword

<https://tih-api.stb.gov.sg/content/v1/venue/search>

Performs a search on all Venues POIs based on keyword as the search parameter. The keyword will match with names, description and tags, returning you the most relevant Venues.

### REQUEST

Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Kallang
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board or HungryGoWhere
nextToken	Next Token which will be used to retrieve the next set of records	No	
sortBy	Field name to sort [name   type   description   origin   source]	No	name
sortOrder	Sort order [asc   desc]	No	asc
language	Language type [en]	No	en

### 3.12. Walking Trails

The APIs listed below allow extraction of Walking Trails POIs and its details (e.g.type, location). Walking Trail POIs can be retrieved by uuid or keyword search.

<div> <div>GET</div> <div> <b>getWalkingTrailByUuids</b>  <a href="https://tih-api.stb.gov.sg/content/v1/walking-trail">https://tih-api.stb.gov.sg/content/v1/walking-trail</a> </div> </div>			
Retrieves the full details of multiple Walking Trails POIs by providing its unique identifier. The acronym for the unique identifier is uuid. This API allows the retrieval of multiple uuids. The uuid is generated while creating new Walking Trails using createWalkingTrail from content provider API. You can retrieve uuids from search Walking Trails API search by keyword.			
REQUEST			
Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify a Walking Trail. This API allows the retrieval of multiple uuids	Yes	009dab0f299aed84f27aa4095c2b03c75c7, 00960bda7cae14842b0938a85344fe12599
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

**GET**

## getWalkingTrailDetailsByUuid

<https://tih-api.stb.gov.sg/content/v1/walking-trail/uuid/{uuid}/detail>

Retrieves the detail of a Walking Trail itinerary by providing Walking Trail unique identifier. The acronym for the unique identifier is uuid. The uuid is generated while creating new Walking Trails using createWalkingTrail from content provider API. You can retrieve uuids from Walking Trails API search by keyword.

### REQUEST

Parameters	Description	Mandatory	Example
uuid	Attribute used to uniquely identify a Walking Trail.	Yes	009dab0f299aed84f27aa4095c2b03c75c7
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

**GET**

## listWalkingTrailTypes

<https://tih-api.stb.gov.sg/content/v1/walking-trail/types>

Retrieve a list of Walking Trail types.

### REQUEST

Parameters	Description	Mandatory	Example
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en

### RESPONSE

Arts; Events & Festivities; Food\_Beverages; History & Culture; See & Do; Shops; Others



<div> <div>GET</div> <div> <b>searchWalkingTrailByKeyword</b>  <a href="https://tih-api.stb.gov.sg/content/v1/walking-trail/search">https://tih-api.stb.gov.sg/content/v1/walking-trail/search</a> </div> </div>			
<p>Performs a search on all Walking Trails POIs based on keyword as the search parameter. The keyword will match with names, description and tags, returning you the most relevant Walking Trails.</p>			
REQUEST			
Parameters	Description	Mandatory	Example
keyword	Keyword to look for when performing the search function	Yes	Heritage
filtersource	Filter the content based on specific source.	No	Singapore Tourism Board
nextToken	Next Token which will be used to retrieve the next set of records.	No	
sortBy	Field name to sort [name   type   description   origin   nearestMrtStation]	No	name
sortOrder	Sort order [asc   desc]	No	asc
language	Language type [en   zh-cn   zh-tw   ja   ko] If no language is supplied, en will be the default language applied.	No	en